



REEL DIA. REF.
Ø.500 [Ø12.7] MIN.
HOLE THRU

DATE	DESCRIPTION	REV.
6.27.19	CHANGE AS PER ECN 19-060 ROTATE TEST PINT IN THE POCKET FOR 90°	A
7.29.19	CHANGE AS PER ECN 19-062 INSULATION MAT'L WAS LCP 30% GLASS FILLED, UL 94V-0	B

PART NO.	BASE COLOR	PART NO.	BASE COLOR
5190TR	RED	5195TR	BROWN
5191TR	BLACK	5196TR	GREEN
5192TR	WHITE	5197TR	BLUE
5193TR	ORANGE	5198TR	GREY
5194TR	YELLOW	5199TR	PURPLE

NOTES:

- SUPPLIED ON TAPE AND REEL ONLY.
- TAPE:
MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
ANSI/EIA-481 STANDARD
- REEL:
7" [180.0] DIA. 1000 PIECES PER REEL

TEST POINT SPECIFICATIONS:

- CONTACT:
MAT'L -.008 [0.20] THK PHOSPHOR BRONZE
FINISH: SILVER PLATE
- INSULATOR:
MAT'L -PA6T, UL 94V-0
(SEE COLOR IN THE TABLE)

THIS DOCUMENT IS THE PROPERTY OF
KEYSTONE ELECTRONICS CORP. AND
SHALL NOT BE REPRODUCED, DISTRIBUTED
OR USED AS A BASIS FOR MANUFACTURE
WITHOUT PRIOR WRITTEN PERMISSION
FROM KEYSTONE ELECTRONICS CORP.

KEYSTONE ELECTRONICS CORP. www.keyeico.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500			
PART NAME			
TEST POINT			
MATERIAL			
AS NOTED			
FINISH			
AS NOTED		DRN BY	DATE
		NT	2.26.19
		AppD	SCALE
		RH	5X
TOLERANCES	INCH	[MM]	CODE
DECIMAL	± .005	[± 0.13]	
ANGULAR	± 1°		
UNLESS OTHERWISE SPECIFIED		C	DWG NO.
			5190TR-5199TR