



Date	SYM	REVISION RECORD	AUTH	DR.	CK.
1/21/06	A	ADDED "ROHS COMPLIANT"	T.B.	B.S.	
9/20/13	B	UPDATED TO ROHS 2 COMPLIANT DIM. 10.7 WAS 11.05 DIM. 12.50 WAS 12.70 DIM. 7.30 WAS 6.10 DIM. 2.50 WAS 3.30	T.B.	B.S.	
12/09/16	C	DIM. 11.30 WAS 12.50	T.B.	B.S.	

Ø7.30 [Ø0.287]

REFERENCE ONLY



FRONT CONTACT




11.3 [0.445]

10.70 [0.421]

REFERENCE ONLY

+0.3
-0.1
Ø2.50 [Ø0.098]



REFERENCE ONLY

NOTES:
MATERIAL: SPRING STEEL WIRE, NICKLE PLTD
ROHS 2 COMPLIANT

Tolerance (Except as noted)	<div><div><div><div></div><div></div><div></div></div><div>MPD</div></div><div>Memory Protection Devices, Inc</div><div>200 Broad Hollow Road, Farmingdale, New York 11735</div></div>		
decimal ±.5 (.020)		Scale	Drawn By B.S.
			Approved By T.B.
Fractional ± .8 (.030)	Title AA BATTERY SPRING CONTACT		
Angular ± 3°	Date 12/09/16	Drawing Number BC-AA	