



SS-132-G-2



ESD-115-TT-05

(2.54 mm) .100"

SS, SD, ESD, ESS, HSS SERIES

PRECISION MACHINED SOCKET STRIPS

Mates with:
TS, TD, HTS, BBS,
BBD, BBL, BDL, BHS

SPECIFICATIONS

For complete specifications see www.samtec.com?SS, www.samtec.com?ESS, www.samtec.com?SD, www.samtec.com?ESD or www.samtec.com?HSS

Insulator Material:
SS, SD, ESS, ESD= Black G.F. Polyester
HSS= Black Liquid Crystal Polymer
Contact:
BeCu
Shell:
Brass except Style 5A
Phosphor Bronze
Plating:
Au over 50 μm (1.27 μm) Ni or Sn over 50 μm (1.27 μm) Ni
Operating Temp Range:
-55 °C to +125 °C
Lead Size Range:
(0.38 mm to 0.56 mm)
.015" to .022" DIA
and most IC leads
RoHS Compliant:
Yes
Lead-Free Solderable:
Wave only



RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



FILE NO. E111594

TYPE STRIP	1	NO. PINS PER ROW	PLATING OPTION	LEAD STYLE	OPTION	OTHER OPTION
		01 thru 32 = SS, ESS Series	-S = 10 μm (0.25 μm) Gold contact, Tin shell (Styles 2 & 22 only)	-T = 30 μm (0.76 μm) Gold contact, Tin shell	-L = Locking Socket Add -L suffix for locking lead socket in end positions. Requires Style -2 or -22 and .035" ± .003" DIA board hole.	-N = Non Flush
		01 thru 36 = HSS, SD & ESD Series	-G = 30 μm (0.76 μm) Gold contact, 10 μm (0.25 μm) Gold shell	-TT = Tin contact and shell (Styles 1, 2, 4, and 05 except LIF N/A)		
	SS = Standard Single Row Socket	HSS = High Temp Single Row Socket				
	ESS = Elevated Single Row Socket					
	SD = Standard Double Row Socket					
	ESD = Elevated Double Row Socket					



Note:
Some lengths, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.

-1A, -1B or -1C
For LIF specify -21A, -21B or -21C (SS, HSS, SD)

LEAD STYLE	Y
-1A or -21A	(9.14) .360
-1B or -21B	(12.95) .510
-1C or -21C	(6.60) .260

-2, -22*, -5A, or -38*
*For LIF specify -22 or -38 (SS, HSS, SD)

LEAD STYLE	X DIA	Y	Z
-2 or -22	(0.51) .020	(3.18) .125	(7.62) .300
-38	(0.51) .020	(4.57) .180	(8.89) .350
-5A	(0.89) .035	(12.95) .510	(17.86) .703

Locking lead available. See OPTION.

-03, -04, -05
For LIF specify -23 (ESS, ESD)

LEAD STYLE	A	B	C
-05	(17.86) .703	(13.46) .530	(4.39) .173
-03 or -23	(11.51) .453	(8.38) .330	(3.12) .123
-04	(14.05) .553	(10.92) .430	(3.12) .123

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Samtec:

[SS-116-G-2](#) [SS-105-G-2](#) [SS-106-G-2](#) [SS-132-G-2](#) [SS-120-S-2](#) [SS-109-T-2](#) [SS-104-G-2](#) [SS-114-G-2](#) [SS-114-S-2](#)
[SS-103-G-2](#) [SS-120-G-2](#) [SS-102-T-2](#) [SS-113-S-2](#) [SS-120-T-2](#) [SS-102-G-2](#) [SS-114-T-2](#) [SS-125-T-2](#) [SS-106-T-2](#)
[SS-110-T-2](#) [SS-107-S-2](#) [SS-113-T-2](#) [SS-116-T-2](#) [SS-112-T-2](#) [SS-132-TT-2](#) [SS-118-T-2](#) [SS-105-T-2](#) [SS-116-T-2-N](#)
[SS-101-TT-2](#) [SS-111-G-2](#) [SS-124-S-2](#) [SS-132-G-2-N](#) [SS-107-TT-2](#) [SS-126-G-2](#) [SS-107-T-2](#) [SS-132-T-2](#) [SS-108-](#)
[T-2-N](#) [SS-112-T-2-N](#) [SS-108-G-2](#) [SS-106-T-2-N](#) [SS-118-T-2-N](#) [SS-103-S-2](#) [SS-112-TT-2-N](#) [SS-110-T-2-N](#) [SS-105-](#)
[T-2-N](#) [SS-112-G-22](#) [SS-132-T-2-N](#) [SS-115-G-2](#) [SS-103-T-2](#) [SS-108-T-2](#) [SS-124-G-2](#) [SS-115-TT-2](#) [SS-112-G-2](#)
[SS-126-S-2](#) [SS-113-G-2](#) [SS-106-T-5](#) [SS-109-G-2](#) [SS-116-TT-2](#) [SS-124-TT-2](#) [SS-103-TT-2](#) [SS-120-T-2-N](#) [SS-110-](#)
[TT-2-N](#) [SS-125-TT-2](#) [SS-106-TT-2](#) [SS-107-T-2-N](#) [SS-104-T-2-N](#) [SS-104-T-2](#) [SS-118-G-2](#) [SS-101-G-2](#) [SS-121-G-2](#)
[SS-109-TT-2](#) [SS-132-G-38](#) [SS-110-S-2](#) [SS-105-TT-2](#) [SS-116-S-2](#) [SS-130-G-2](#) [SS-107-G-2](#) [SS-122-T-2](#) [SS-108-](#)
[S-2](#) [SS-111-T-2](#) [SS-101-T-2](#) [SS-112-S-2](#) [SS-125-G-2](#) [SS-104-S-2](#) [SS-115-T-2](#) [SS-101-S-2](#) [SS-106-S-2](#) [SS-105-S-](#)
[2](#) [SS-130-T-2-N](#) [SS-102-TT-2](#) [SS-109-S-2](#) [SS-125-S-2](#) [SS-108-TT-2](#) [SS-123-TT-2](#) [SS-102-S-2](#) [SS-104-TT-2](#) [SS-](#)
[108-TT-2-N](#) [SS-110-TT-2](#) [SS-120-TT-2](#) [SS-128-G-2](#) [SS-114-TT-2](#)