

Specifications

Specifications are subject to change without notice.

Model/PN	Basic (BC3)	Smart (SC3)	Intelligent (IC3)
Application	Residential/Commercial		Commercial
Voltage (Vac)	208 / 240 Vac ± 10%, 1-phase		
Frequency (Hz)	60 Hz ± 10%		
Current (rms)	32A		
Charging Connector	SAE J1772 Type 1		
Charging Cable Length	18 ft. (25 ft. optional)		
Metering Accuracy	N/A	Embedded, ± 1%	
Real Time Clock	N/A	Yes (min. 7 days)	
Indications	LED x1 with multiple colors (RGB) ● STEADY GREEN - standby SLOW FLASH GREEN - EV connected FAST FLASH GREEN - authenticating ● SLOW FLASH BLUE - charging ● SLOW FLASH RED - recoverable fault STEADY RED - unrecoverable fault		
Wi-Fi	N/A	802.11 b/g/n	
4G	N/A	LTE Cat.1 (AT&T or Verizon)	
RFID	N/A	ISO 14443 A/B - ISO 15693	
Display	N/A	Dot-matrix (2 lines)	
Data Protocol	N/A	OCPP 1.6J (OCPP 1.5J optional)	
Operation Temp.	-30 °C ~ 50 °C / -22 °F ~ 122 °F		
Storage Temp.	-40 °C ~ 70 °C / -40 °F ~ 158 °F		
Mounting Type	Wall (default) / Pole		
Installation Type	NEMA 6-50		Hardwired
IP Performance	NEMA 4		
Impact Resistance	IK10		
Dimension (H x W x D, inch)	11.14 x 7.56 x 3.11		
Web Portal Management	N/A	Yes	
Console Management	Yes		
Certification	UL 2231/2594 - FCC Part 15B		

Dimension Details



For more product information and sales inquiries:

LITEON®

LITE-ON TECHNOLOGY CORP.

- www.liteon.com
- +886-2-2222-6181 ext.3053
- +886-2-2226-3559
- CES@liteon.com
- 4F, No.90, Chien 1 Road, Chung Ho, New Taipei City 23585, Taiwan, R.O.C

US office

- +1 818-216-5776 / (469) 331-9838
- 3001 Summit Ave Ste 400 Plano, TX 75074



Visit us

Lite-On Charger (not to scale)

