



DOW™ 20 Series Ultra-Pure Polyethylene is produced using a proprietary process that produces a stress-crack resistant, ultra-pure LDPE with very high molecular weight, narrow molecular weight distribution and few short chains. Used in pharmaceutical packaging squeeze bottles and personal care tubes.

GRADE	MELT INDEX dg/min 190C/2.16kg	DENSITY g/cm3	APPLICATION	PROCESING METHOD
20	1.9	0.920	Inhalation Drug Vials	Blow-Fill-Seal, Film
2010	1.9	0.920	Caps, Tips	Injection Molding
20-6064	1.9	0.920	Ophthalmic Squeeze Bottles	Injection Blow Molding

Common Applications



Inhalation Drug Vials



Ophthalmic Squeeze Bottle



Tubes For Personal Care Products



Tips & Caps

®™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

The information provided in this document is for informational purposes only and does not constitute a product specification. The information is subject to change without notice. Entec Polymers, LLC makes no representation as to the accuracy and assumes no obligation to liability for the information, including without limitation its content, any advice given, or the results obtained. ENTEC DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE. The customer shall use its own independent skill and expertise in the evaluation of the resin product to determine suitability for a particular application and accepts the results at its sole risk.