



SINAMICS LINE REACTOR 380-480V 3AC 47-63HZ I_{LN} = 11,3A
STANDALONE

Order number	6SL3203-0CE21-0AA0
Phase number / of the input voltage	3
Type of voltage / of the input voltage	AC
Input voltage	380 ... 480
Output current / Rated value	11.3 A
Active power loss	
• at 50 Hz	Wert fehlt!
• at 60 Hz	Wert fehlt!
Type of electrical connection	
• for mains supply line	screw-type terminal
• for load-side outgoing feeder	screw terminals
Type of connectable conductor cross-section / for load-side outgoing feeder	Wert fehlt!
Connectable conductor cross-section	
• for mains supply line	4 mm ²
• for load-side outgoing feeder	4 mm ²
Type of electrical connection / for PE conductor	M4 x 8, washer, spring lock washer
Protection class IP	IP20
Width	125 mm
Height	140 mm
Depth	71 mm
Net weight	2.1 kg
Certificate of suitability	cURus

Further information

Information und Download Center

https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx

Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Cataog/Product/6SL32030CE210AA0/all>

Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SL32030CE210AA0/all>