

PRODUCT-DETAILS

ACS580-04-585A-4

ACS580-04-585A-4 PN: 315 kW, IN: 585 A



General Information

Global Commercial Alias	ACS580-04-585A-4
Product ID	3AUA0000170521
ABB Type Designation	ACS580-04-585A-4
EAN	6438177340430
Catalog Description	ACS580-04-585A-4 PN: 315 kW, IN: 585 A

Long Description	The ACS580-04 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture. All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Versatile and straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance, while rugged and robust design makes it a good fit for various environments. With the ACS580 drives you can easily take full control of your processes to comprehensively manage your plant. The ACS580-04 drive module comes in IP00 enclosure as standard for cabinet installation. Also, IP20 enclosure is available.
------------------	--

Ordering

Country of Origin	Finland (FI)
Customs Tariff Number	85044088
Invoice Description	ACS580-04-585A-4 PN: 315 kW, IN: 585 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece

Quote Only	No
Selling Unit of Measure	piece

Container Information

Gross Volume	0.19 m ³
--------------	---------------------

Dimensions

Product Net Weight	162 kg
Product Net Height	1462 mm
Product Net Length	529 mm
Product Net Width	350 mm
Package Level 1 Depth / Length	2060 mm
Package Level 1 Height	500 mm
Package Level 1 Width	670 mm
Package Level 1 Units	1 carton

Technical

Number of Phases	3
Degree of Protection	IP00
Enclosure Type NEMA	Open Type
Frequency (f)	50/60 Hz
Input Voltage (U _{in})	380 ... 480 V
Mounting Type	Module for cabinet building
Output Current, Heavy-Duty Use	429 A
Output Current, Light-Overload Use	575 A
Output Current, Normal Use	585 A
Output Power, Heavy-Duty Use	250 kW
Output Power, Light-Overload Use	315 kW
Output Power, Normal Use	315 kW
Apparent Power Output	405 kV·A
Efficiency Level	IE2
Standby Loss	396 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	1797 W	0.4 %	92.3 %
0 / 50 %	2589 W	0.6 %	94.3 %
0 / 100 %	4812 W	1.2 %	94.6 %
50 / 25 %	1945 W	0.5 %	95.9 %
50 / 50 %	2908 W	0.7 %	96.8 %
50 / 100 %	5580 W	1.4 %	96.9 %
90 / 50 %	3358 W	0.8 %	97.9 %
90 / 100 %	6828 W	1.7 %	97.9 %

Temperature Rating	Maximum 40 °C
--------------------	---------------

Additional Information	
Product Main Type	ACS580-04
Product Name	Frequency converter

Classifications	
UNSPSC	39122001

Environmental	
SCIP	58f22844-2faf-42d0-845e-c7388e32f3e4 Finland (FI)
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Drives → Low voltage AC drives → General purpose drives → ACS580-04 - Drive module

