

## 2025 Subaru Forester Wilderness Specifications

<b>Vehicle type</b>	5-passenger sport utility vehicle
<b>Engine</b>	4-cyl. horizontally opposed (BOXER), aluminum cylinder block and cylinder heads
Displacement	2,498 cc / 152 cu. in.
Bore x Stroke	94.0mm x 90.0mm / 3.70 in. x 3.54 in.
Compression ratio	12.0:1
Horsepower	182 @ 5,800 rpm
Torque	176 lb.-ft. @ 4,400 rpm
Fuel system	Direct fuel injection, electronic throttle control
Fuel requirement	Regular grade, minimum 87 AKI
Valvetrain	Double overhead chain-driven camshafts (DOHC), 4 valves per cylinder, Dual Active Valve Control System (DAVCS) controls valve timing on intake and exhaust camshafts, tumble generator valves
Ignition	Direct
<b>Transmission</b>	Lineartronic® CVT (continuously variable transmission) with 8-speed manual shift mode and steering wheel paddle shift control switches.
Transmission ratios	8-speed manual control mode, Wilderness
1	4.066
2	2.628
3	1.911
4	1.490
5	1.166
6	0.914
7	0.717
8	0.559
Rev.	4.379
Final drive ratio	4.111
<b>Symmetrical All-Wheel Drive</b>	Active Torque Split All-Wheel Drive with electronically managed continuously variable hydraulic transfer clutch that actively manages the torque split based on acceleration, deceleration and available traction. System continuously powers all four wheels and will transfer torque to the wheels with the best grip.  Wilderness-exclusive Dual-mode, Dual-function X-MODE features Snow / Dirt mode, Deep Snow/ Mud mode (under 25 mph); Deep Snow / Mud mode (above 25 mph); Low Speed / Low Ratio Gradient Control can automatically detect vehicle travel on steep gradients and shift to a CVT low ratio comprised of a lower transfer gear ratio and lower first ratio. Hill Descent Control standard
Dynamic controls	Vehicle Dynamics Control (VDC) with electronic traction control (TCS) and rollover sensor Active Torque Vectoring (using brakes)
<b>Chassis</b>	Unitized body construction, Subaru Global Platform
Suspension	4-wheel independent, raised with 9.2-in. ground clearance
Front	MacPherson-type struts, lower L-arms, coil springs, stabilizer bar, hydraulic engine mounts
Rear	Double wishbone, coil springs, stabilizer bar

Brakes	Electronically controlled power-assisted, dual diagonal-wheel disc brake system with Electronic Brake-force Distribution (EBD) and 4-channel / 4-sensor ABS with Brake Assist and Brake Override safety systems; Active Torque Vectoring; Auto Vehicle Hold; Electronic Parking Brake Front brakes: 12.4-in. ventilated discs Rear brakes: 11.2-in. ventilated rear discs
Steering	Electric Power Assisted rack-and-pinion Ratio: 13.0:1 Turns, lock-to-lock: 2.6 Turning circle: 35.4 ft.
Wheels	17 x 7-in., matte black finish
Tires	Yokohama Geolandar A/T 225/60R17 99T all-terrain raised white letter tires, includes full-size spare
<b>Exterior Dimensions</b>	
Wheelbase	104.9 in.
Length	182.7 in.
Width	Width: 72.2 in. With mirrors: 81.3 in.
Height	68.9 in. (roof rails standard)
Min. road clearance	9.2 in.
Angle of approach	23.5 deg.
Angle of departure	25.4 deg.
Ramp breakover angle	21.0 deg
Track (front/rear)	61.4/61.4 in.
Curb weight (lbs.) with standard equipment	3,620 lbs.
<b>Interior Dimensions</b>	
Headroom (f/r)	40.2 in./37.6 in.
Legroom (f/r)	43.3 in./39.4 in.
Hip room (f/r)	54.5 in./53.5 in.
Shoulder room (f/r)	58.1 in./57.2 in.
EPA interior volume	107.6 cu. ft.
Cargo volume	Rear seatbacks up: 26.9 cu. ft. Rear seatbacks down: 69.1 cu. ft.
Cargo liftover height	29.1 in.
Cargo area height	32.4 in.
Cargo area width between wheel housings	43.3 in.
Max. load length at floor	Rear seatbacks up: 35.7 in. Rear seatbacks down: 69.9 in.
Rear gate max opening width	51.2 in. (at lower area: 49.5 in.)
Rear gate opening height	32.2 in.
<b>Fuel economy</b>	
EPA-estimated city/highway/combined mpg	25 city/28 highway/26 combined
Fuel tank capacity	16.6 gal.