

2026 Subaru Impreza Specifications

Vehicle type	5-door, 5-passenger hatchback	
Engine	Sport	RS
Displacement	1,995 cc / 122 cu. in.	2,498 cc / 152 cu. in
Bore x Stroke	84.0 mm x 90.0 mm / 3.31 in. x 3.54 in.	94.0 mm x 90.0 mm / 3.70 in. x 3.54 in.
Compression ratio	12.5:1	12.0:1
Horsepower	152 hp @ 6,000 rpm	180 hp @ 5,800 rpm
Torque	145 lb.-ft. @ 4,000 rpm	178 lb.-ft. @ 3,700 rpm
Fuel system	Direct fuel injection, electronic throttle control	
Fuel requirement	Regular grade, minimum 87 AKI	
Valvetrain	Double overhead chain-driven camshafts (DOHC), 4 valves per cylinder, Dual Active Valve Control System controls valve timing on intake and exhaust camshafts; tumble generator valves	
Ignition	Direct	
Powertrain management	<ul style="list-style-type: none"> • Auto Stop-Start system fuel-saving technology • Sport and RS: Subaru SI-DRIVE driver selectable powertrain management system with Intelligent and Sport modes and steering wheel control switches 	
Transmission	Lineartronic® CVT (continuously variable transmission) with 8-speed manual mode and steering wheel paddle shift control switches	
Transmission ratios	8-speed manual control mode (Sport, RS)	
1	4.066	4.066
2	2.628	2.646
3	1.911	1.965
4	1.535	1.532
5	1.195	1.199
6	0.914	0.939
7	0.717	0.729
8	0.559	0.559
Rev.	4.379 (all)	

Final drive ratio	3.700 (all)
Symmetrical All-Wheel Drive	Standard on all models: ACT-4 Active Torque Split All-Wheel Drive with electronically controlled variable hydraulic transfer clutch
Stability/traction control	Vehicle Dynamics Control (VDC) with all-wheel, all-speed traction control (TCS) and rollover sensor
Chassis	Unitized body construction, full inner frame safety structure
Suspension	4-wheel independent
Front	MacPherson-type struts, lower L-arms, coil springs, dampers, stabilizer bar, hydraulic engine mounts
Rear	Double wishbone, coil springs, dampers, stabilizer bar
Brakes	Electronically controlled power-assisted dual diagonal-wheel disc brake system with Electronic Brake-force Distribution and 4-channel / 4-sensor ABS with Brake Assist and Brake Override safety systems; Active Torque Vectoring; Auto Vehicle Hold; Incline Start Assist; Electronic Parking Brake Front ventilated discs: 12.4-in. ventilated discs with dual-piston calipers Rear ventilated discs: 11.2-in. ventilated discs with single-piston calipers
Steering	Electric Power Assisted rack-and-pinion (dual-pinion) Ratio: 13.0:1 Turns, lock-to-lock: 2.5 Turning circle: 34.8 ft.
Wheels	18 x 7.5-in. aluminum alloy
Tires	225/40R18 88V all-season
Exterior Dimensions	
Wheelbase	105.1 in.
Length	176.2 in.
Width	70.1 in. (with mirrors: 79.4 in.)
Height	58.3 in.
Min. road clearance	5.1 in.
Track (front/rear)	60.6/60.8 in.
Curb weight (lbs.) with standard equipment	Sport: 3,249 lbs. (3,280 lbs. with option package) RS: 3,275 lbs. (3,323 lbs. with option package)
Interior Dimensions	
Headroom (f/r)	39.8 in./38.0 in. (With moonroof: 38.7 in./38.0 in.)
Legroom (f/r)	42.9 in./36.5 in.
Hip room (f/r)	55.1 in./53.2 in.
Shoulder room (f/r)	56.8 in./55.3 in.
EPA interior volume	Base: 100.5 cu. ft. (With moonroof: 99.0 cu. ft.)
Cargo volume	Rear seatbacks up/down: 20.4 cu. ft./56.0 cu. ft.
Cargo liftover height	26.0 in.
Max. load length at floor	Rear seatbacks up/down: 32.1 in./63.9 in.
Fuel economy	
EPA-estimated city/highway/combined mpg	TBD
Fuel tank capacity	16.6 gal.

