

## 2021 Subaru Legacy® Specifications

	2.5L Models	XT Models
<b>Vehicle type</b>	5-passenger sedan	
<b>Engine</b>	DOHC 16V 4-cylinder BOXER; aluminum cylinder heads and block	DOHC 16V 4-cylinder BOXER, aluminum cylinder block and cylinder heads, twin-scroll turbocharger, intercooler
Bore x Stroke	94 x 90mm	94 x 86mm
Displacement	2,498cc (152 cu. in.)	2,387 cc (146 cu. in.)
Compression ratio	12.0:1	10.6:1
Valvetrain	Chain-driven camshafts, Dual Active Valve Control System (intake and exhaust valves)	Chain-driven camshafts, Dual Active Valve Control System (intake and exhaust valves)
Horsepower	182 hp @ 5,800 rpm	260 hp @ 5,600 rpm
Torque	176 lb-ft @ 4,400 rpm	277 lb-ft @ 2,000-4,800 rpm
Fuel/induction	Sequential multi-port fuel injection (MFI) with cylinder head direct injection and Electronic Throttle Control (ETC) system	Sequential multi-port fuel injection (MFI) with cylinder head direct injection and Electronic Throttle Control (ETC) system
Fuel requirement	Regular grade, 87 AKI minimum	
<b>Drivetrain</b>		
Transmission	Lineartronic® CVT (Continuously Variable Transmission) includes 8-speed steering wheel paddle control switches	High-torque Lineartronic® CVT includes 8-speed steering wheel paddle control switches
Gear ratios, manual mode	1 4.066 2 2.600 3 1.827 4 1.377 5 1.061 6 0.836 7 0.668 8 0.559 R 4.379	3.229 2.310 1.654 1.278 0.985 0.768 0.604 0.468 3.139
Final drive	3.700	3.900
Symmetrical AWD	Active Torque Split AWD with electronically managed variable hydraulic transfer clutch	
Stability control	Vehicle Dynamics Control (VDC) with electronic traction control system (TCS) and Active Torque Vectoring	

<b>Chassis</b>	Unitized body construction, Ring-shaped Reinforcement Frame safety structure	
Suspension	Front: MacPherson-type struts with internal rebound springs, aluminum lower L- arms, and stabilizer bar  Rear: Double wishbone with subframe, coil springs and stabilizer bar	
Brakes	Power-assisted 4-wheel disc with Electronic Brake-force Distribution (EBD), 4-channel / 4-sensor ABS, Brake Assist Control, Brake Override system and Auto Vehicle Hold (AVH) Front: Dual piston calipers, ventilated discs: 12.4 in. Rear: Single-piston calipers, ventilated discs: 11.8-in.	
Steering	Quick-ratio electric power-assisted rack and pinion	
Ratio	13.5:1	
Turns, lock to lock	2.7	
Turning circle	36.8 ft. curb-to-curb	
Wheels	<u>Base</u> 17 x 7-in. steel 17 x 7.5-in. alloy, black with machine finish (option)  <u>Premium</u> 17 x 7.5-in. alloy, black with machine finish  <u>Sport</u> 18 x 7.5-in. alloy, black finish  <u>Limited</u> 18 x 7.5-in. alloy, black with machine finish	<u>Limited XT, Touring XT</u> 18 x 7.5-in. alloy, black with machine finish
Tires	Base and Premium: 225/55R17 97V Sport and Limited: 225/50R18 95V All-season for all models	225/50R18 95V all season
<b>Exterior Dimensions</b>		
Wheelbase	108.3 in.	
Length	190.6 in.	
Height	59.1 in.	
Width	72.4 in. (81.8 in. with mirrors)	
Overhang (f/r)	39.8 in. / 42.5 in.	
Track (f/r)	62.2 in. / 63.4 in.	
Base curb weight (lb.)	Base: 3,500 Premium: 3,504 Sport: 3,524 Limited: 3,531	XT Limited: 3,779 XT Touring: 3,790

<b>Interior Dimensions</b>		
Head room (f/r)	39.4 in. / 37.3 in. With moonroof: 37.3 in. / 37.2 in.	
Leg room (f/r)	42.8 in. / 39.5 in.	
Shoulder room (f/r)	58.1 in. / 57.4 in.	
Hip room (f/r)	55.5 in. / 54.8 in.	
EPA passenger volume	105.5 cu. ft. (without moonroof) 102.5 (with moonroof)	
EPA trunk capacity	15.1 cu. ft.	
EPA total volume	120.6 (without moonroof) 117.6 (with moonroof)	
Trunk liftover height	26.8 in.	
<b>Fuel Economy</b>	<b>2.5L models</b>	<b>XT models</b>
EPA estimated city / highway mpg	27/35/30	24/32/27
Fuel capacity	18.5 gal.	