



Binding Diameter Guide

Thickness Of Materials To Be Bound (Including Covers)	Use This Diameter Of EZ Coil (mm)	Element Diameter (Inches)	Number Of Sheets 50 lb Offset Or 20 lb Bond
---	---	---------------------------------	---

Pitch				
5:1	4:1			
1/8	1/8	6 mm	1/4"	30
5/32	5/32	7 mm	9/32"	40
3/16	3/16	8 mm	5/16"	50
7/32	7/32	9 mm	11/32"	60
9/32	9/32	10 mm	3/8"	70
5/16	5/16	11 mm	7/16"	80
11/32	11/32	12 mm	15/32"	90
3/8	3/8	13 mm	1/2"	100
7/16	7/16	14 mm	9/16"	110
1/2	1/2	16 mm	5/8"	125
9/16	9/16	18 mm	11/16"	140
5/8	5/8	20 mm	3/4"	160
---	11/16	22 mm	7/8"	180
---	13/16	25 mm	1"	210
---	15/16	28 mm	1-1/8"	230
---	1	30 mm	1-3/16"	250
---	1-1/16	32 mm	1-1/4"	265
---	1-5/16	35 mm	1-3/8"	270
---	1-3/8	38 mm	1-1/2"	280
---	1-5/8	40 mm	1-11/16"	300
---	1-3/4	45 mm	1-7/8"	390
---	1-7/8	50 mm	2"	470

Note: The above column "Number Of Sheets" is a general guideline only.
 Paper will vary in thickness depending on type, grade and moisture content.

To estimate EZ Coil diameter, add total material thickness **plus**
 2 mm for size 6 mm
 3 mm for sizes 7, 8, 9, 10, 11, 12, 13, 14 and 16 mm
 4 mm for sizes 18, 20 and 22 mm
 5 mm for sizes 25, 28, 30, 32, 35, 38, 40, 45 and 50 mm

Standard EZ Coil lengths are 12" and 36" (which yields three 12" long elements), although EZ Coil can be produced in any custom length.
 35, 38, 40, 45 and 50 mm are available in 12" lengths only.
 Add 1" to length of binding edge to determine correct length needed.