


**SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT IDENTIFIER	CelaBrew® CB-3
CHEMICAL NAME	Diatomaceous Earth, Calcined
CHEMICAL FAMILY	Silica
MATERIAL USE	Filter Aid, functional filler
RESTRICTION ON USE	None Known
MANUFACTURER	EP Minerals, LLC., 9785 Gateway Dr., Reno, NV 89521
TELEPHONE NO.	(775) 824 7600 (Monday – Friday 8:00 am PST – 5:00 pm PST)
EMERGENCY TELEPHONE NO.	(775) 824 7600 (Monday – Friday 8:00 am PST – 5:00 pm PST)
SDS DATE OF PREPARATION	July 23, 2025

**SECTION 2: HAZARDS IDENTIFICATION**

OSHA GHS HAZARD CLASSIFICATION	Carcinogen Category 1A Specific Target Organ Toxicity, Repeated Exposure Category 1
HAZARDS NOT OTHERWISE CLASSIFIED	None
LABEL ELEMENTS	<p><b>DANGER</b>  May cause cancer by inhalation.  Causes damage to lungs through prolonged or repeated exposure.  Obtain special instructions before use.  Do not handle until all safety precautions have been read and understood.  Do not breathe dust.  Wear eye protection.  If exposed or concerned: Get medical advice.  Dispose of contents in accordance with local, state and federal regulations.</p> 

**SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

INGREDIENT IDENTIFICATION	APPROXIMATE CONCENTRATION (%)	C.A.S. NUMBERS
Diatomaceous Earth, Calcined (kieselguhr) (contains 10-40% Crystalline Silica - Cristobalite)	100%	91053-39-3 14464-46-1

**SECTION 4: FIRST AID MEASURES**

EYE	Flush eyes with generous quantities of water or eye rinse solution. Consult physician if irritation persists.
SKIN	Use moisture renewing lotions if dryness occurs.
INGESTION	Drink generous amounts of water to reduce bulk and drying effects.
INHALATION	Remove to fresh air. Blow nose to evacuate dust.
Most important symptoms/effects, acute and delayed	Dust may cause abrasive irritation to eyes. Prolonged skin contact may cause dryness. Dust may cause nose, throat and upper respiratory tract irritation. Prolonged inhalation of respirable dust containing silica may cause a progressive lung disease, silicosis and lung cancer. See Section 11 for additional information.
Indication of immediate medical attention and special treatment, if necessary	Immediate medical attention is not normally required. If dust irritates the eyes, seek medical attention.

MATERIAL NAME	CelaBrew® CB-3			Page 2 of 4
SECTION 5: FIRE FIGHTING MEASURES				
EXTINGUISHING MEDIA	Not applicable, the material is not combustible.			
SPECIFIC HAZARDS ARISING FROM THE CHEMICAL	Not applicable, the material is not combustible.			
SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS	Not applicable, the material is not combustible.			
SECTION 6: ACCIDENTAL RELEASE MEASURES				
PERSONAL PRECAUTIONS	If dust is present, use respirator fitted with particulate filter as specified in Section 8. Protect eyes with goggles. Do not breathe dust.			
ENVIRONMENTAL PRECAUTIONS	This material is not a significant environmental concern.			
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	Vacuum clean spillage or wet sweep. Avoid creating airborne dust. Place in a container for use or disposal.			
SECTION 7: HANDLING AND STORAGE				
PRECAUTIONS FOR SAFE HANDLING	Minimize dust generation. Avoid contact with eyes. Do not breathe dust. Repair or dispose of broken bags. Observe all label precautions and warnings. In the U.S. refer to the OSHA Respirable Crystalline Silica Standards; 29CFR1910.1053, 1915.1053 and 1926.1053 for specific handling and use requirements.			
CONDITIONS FOR SAFE STORAGE	Store in a dry place to maintain packaging integrity and product quality. Do not store near hydrofluoric acid or concentrated caustic solutions.			
SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION				
EXPOSURE GUIDELINES:				
Component	OSHA PEL	ACGIH TLV	MSHA PEL	NIOSH REL
Diatomaceous Earth, Calcined (kieselguhr)	5 mg/m³ respirable dust 15 mg/m³ total dust	None Established	5 mg/m³ respirable dust 15 mg/m³ total dust	None Established
Crystalline Silica (Cristobalite)	0.05 mg/m3 Respirable dust	0.025 mg/ m3 Respirable dust	1 x 30 mg/m3 2 % SiO2+2 total dust  1 x 10 mg/m3 2 % SiO2+2 Respirable dust	0.05 mg/ m3 Respirable dust
ENGINEERING CONTROLS	Use general or local exhaust ventilation to control dust within recommended exposure limits. Refer to ACGIH publication “Industrial Ventilation” or similar publications for design of ventilation systems.			
PERSONAL PROTECTIVE EQUIPMENT:				
EYE / FACE PROTECTION	Goggles to protect from dust			
SKIN PROTECTION	No special equipment is needed.			
RESPIRATORY PROTECTION	Respirators fitted with filters certified to standard 42CFR84 under series N95 should be worn when dust is present. If the dust concentration is less than ten (10) times the Permissible Exposure Limit (PEL) use a quarter or half-mask respirator with a N95 dust filter or a single use dust mask rated N95. If dust concentration is greater than ten (10) times and less than fifty (50) times the PEL, a full-face piece respirator fitted with replaceable N95 filters is recommended. If dust concentration is greater than fifty (50) and less than two hundred (200) times the PEL use a power air-purifying (positive pressure) respirator with a replaceable N95 filter. If dust concentration is greater than two hundred (200) times the PEL use a type C, supplied air respirator (continuous flow, positive pressure), with full face piece, hood or helmet.			
GENERAL HYGIENE	Avoid breathing dust. Avoid contact with eyes. Wash hands after handling and before eating or drinking.			

MATERIAL NAME	CelaBrew® CB-3		Page 3 of 4
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES			
PHYSICAL STATE	Solid	COLOR	Buff to pink powder
ODOR	Odorless	pH (10% SUSPENSION)	7
MELTING POINT/FREEZING POINT:	> 1300° C	BOILING POINT/RANGE	Not applicable
FLASH POINT	Not applicable	EVAPORATION RATE	Not applicable
FLAMMABLE LIMITS: LEL	Not applicable	UEL	Not applicable
VAPOR PRESSURE	Not applicable	RELATIVE VAPOR DENSITY	Not applicable
DENSITY / RELATIVE DENSITY	2.2	SOLUBILITY(IES):	< 1% (water)
PARTITION COEFFICIENT: n- OCTANOL/WATER:	Not applicable	AUTO-IGNITION TEMPERATURE	Not applicable
DECOMPOSITION TEMPERATURE	> 1300° C	FLAMMABILITY	Not applicable
PARTICLE CHARACTERISTICS	Not determined	KINEMATIC VISCOSITY	Not applicable
SECTION 10: STABILITY AND REACTIVITY			
REACTIVITY	Material is not reactive.		
CHEMICAL STABILITY	Material is stable.		
POSSIBILITY OF HAZARDOUS REACTIONS	Material is not reactive under normal conditions of handling unless mixed with incompatible substances below.		
CONDITIONS TO AVOID	Not applicable		
INCOMPATIBLE MATERIALS	Hydrofluoric acid and concentrated caustic solutions may react violently with the product.		
HAZARDOUS DECOMPOSITION PRODUCTS	Not applicable		
SECTION 11: TOXICOLOGICAL INFORMATION			
POTENTIAL HEALTH EFFECTS			
Likely Routes of Exposure	See below		
EYE	May cause irritation (tear formation and redness) if dust gets in eyes.		
SKIN	Not absorbed by the skin, but may cause dryness if prolonged exposure.		
INGESTION	Ingestion of small quantities is not considered harmful, but may cause irritation of the mouth, throat and stomach.		
INHALATION	Acute inhalation can cause dryness of the nasal passage and lung congestion, coughing and general throat irritation. Acute inhalation of high concentrations of respirable crystalline silica may cause acute silicosis.		
CHRONIC EFFECTS	This product contains crystalline silica. Respirable crystalline silica may cause lung cancer and lung disease (silicosis) if inhaled for prolonged periods. Symptoms of silicosis include wheezing, cough and shortness of breath.		
CARCINOGENICITY	Calcined diatomaceous earth (Kieselguhr) is composed of amorphous and crystalline silica. Respirable crystalline silica (cristobalite) is classified by IARC and NTP as a known human carcinogen. Crystalline silica is only known to cause cancer when inhaled in a respirable form. It is not known to cause cancer by any other route of exposure.		
NTP	Respirable crystalline silica (cristobalite) is classified as a known human carcinogen.		
IARC	Respirable crystalline silica (cristobalite) is classified as a known human carcinogen.		
NUMERICAL MEASURES OF TOXICITY	No data available		
CORROSIVENESS, SENSITIZATION, IRRITANCY	Not applicable		

MATERIAL NAME		CelaBrew® CB-3		Page 4 of 4							
REPRODUCTIVE TOXICITY		Not available									
TERATOGENICITY, MUTAGENICITY		Not available									
SECTION 12: ECOLOGICAL INFORMATION											
ECOTOXICITY:		Diatomaceous earth products have shown some efficacy as a natural insecticide, but otherwise have no demonstrated toxicity in regards to aquatic or terrestrial life.									
PERSISTENCE AND DEGRADABILITY		Non-biodegradable, inert.									
BIOACCUMULATIVE POTENTIAL		Little potential for bioaccumulation									
MOBILITY IN SOIL		No mobility									
OTHER ADVERSE EFFECTS		None known									
SECTION 13: DISPOSAL CONSIDERATIONS											
WASTE DISPOSAL		If this material as supplied becomes a waste, use solid waste disposal common to landfill type operations or in slurry to sumps. Not considered a hazardous waste under RCRA (40CFR Part 261).									
PACKAGING DISPOSAL		Dispose of in accordance with applicable laws and regulations, typically solid waste disposal common to landfill type operations.									
SECTION 14: TRANSPORT INFORMATION											
UN NUMBER		Not applicable									
UN PROPER SHIPPING NAME		Not regulated									
TRANSPORT HAZARD CLASSES(ES)		Not classified									
PACKING GROUP, IF APPLICABLE		Not applicable									
ENVIRONMENTAL HAZARDS		Not a marine pollutant									
TRANSPORT IN BULK ACCORDING TO IMO INSTRUMENTS:		Not determined									
SPECIAL PRECAUTIONS		None (no placarding or special handling required)									
SECTION 15: REGULATORY INFORMATION											
U.S. FEDERAL:											
TSCA		Diatomaceous Earth and Cristobalite appear on the EPA TSCA inventory list.									
CERCLA		Diatomaceous Earth is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR 302.									
SARA TITLE III		Not listed.									
California Proposition 65:		⚠ <b>WARNING:</b> This product can expose you to crystalline silica, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .									
SECTION 16: OTHER INFORMATION											
				<table border="1"> <tr> <td rowspan="4">HMIS</td> <td>0* Health</td> <td rowspan="4"></td> </tr> <tr> <td>0 Flammability</td> </tr> <tr> <td>0 Reactivity</td> </tr> <tr> <td>E Protective Equipment</td> </tr> </table>		HMIS	0* Health		0 Flammability	0 Reactivity	E Protective Equipment
HMIS	0* Health										
	0 Flammability										
	0 Reactivity										
	E Protective Equipment										
DATE OF PREPARATION		July 23, 2025									
REVISION		Update to OSHA Hazardous Communication Standard 2024									

**Disclaimer:** As of the date of the preparation of this document, the foregoing information is believed to be accurate and is provided in good faith to comply with applicable federal and state laws. No warranty, representation or guaranty of any kind, express or implied, is hereby provided or intended with respect to the completeness of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by the purchase, resale, use or exposure to our product. Customer users of silica must comply with all applicable health and safety laws, regulations and orders, including OSHA Hazardous Communication Standard.