

SUPERSTOR ULTRA EVO STORAGE

Storage Tanks



Features

- **STAINLESS STEEL** tank constructed of high-quality, lightweight stainless steel making it easier to handle than glass-lined water heaters.
- **IMMERSION CONTROL WELL** stainless steel sensor well provides accurate temperature control.
- **RECIRCULATION PORT** - ensures quick hot water delivery, reducing water waste and improving thermal efficiency.
- **TEMPERATURE AND PRESSURE RELIEF VALVE** - included for ease of installation.

Performance

- **ENVIRONMENTALLY SAFE CFC FOAM 2+ INCHES OF SUPER FOAM INSULATION FOR LOW STANDBY LOSS**
- **NSF 5 CERTIFIED**

Quality

- **444 STAINLESS STEEL TANK**
- **THOROUGH TREATMENT METHODS** are applied to improve durability and enhance corrosion resistance.
- **NO ANODE ROD NEEDED**
- **10 YEAR TANK WARRANTY FOR RESIDENTIAL AND COMMERCIAL USE**



SPECIFICATIONS AND APPLICATION DATA

MODELS	NOMINAL CAPACITY (GAL.)	WORKING PRESSURE (PSI)	CONNECTION SIZES (SIDE)	CONNECTION SIZES (FRONT)
SSU-EVO 30CB	30	150	3/4" NPT FEMALE	3/4" NPT FEMALE
SSU-EVO 45CB	39	150	3/4" NPT FEMALE	3/4" NPT FEMALE
SSU-EVO 60CB	55	150	3/4" NPT FEMALE	3/4" NPT FEMALE
SSU-EVO 80CB	75	150	1-1/2" NPT FEMALE	1-1/2" NPT FEMALE
SSU-EVO 119CB	117	150	1-1/2" NPT FEMALE	1-1/2" NPT FEMALE

DIMENSIONS & WEIGHT

MODEL	PRODUCT DIAMETER (IN) A	INLET/DRAIN (IN) B	BOILER RETURN (IN) C	OUTLET/T&P HEIGHT (IN) D	PRODUCT HEIGHT (IN) E	CONTROL WELL HEIGHT (IN) F	RECIRCULATING PORT (IN) G	SHIPPING WEIGHT (LBS)
SSU-EVO 30CB	19 3/8	8	18	33 1/2	42 3/8	15	28 1/2	66
SSU-EVO 45CB	19 3/8	8	18	44 3/8	54 3/8	15	32 1/2	80
SSU-EVO 60CB	23	8 3/8	18 3/8	43 3/8	52 3/8	15 3/8	32 3/8	91
SSU-EVO 80CB	23	8 3/8	18 3/8	59 3/8	72	15 3/8	37 3/8	113
SSU-EVO 119CB	28 3/8	9 3/8	19 3/8	56 3/8	74	16 3/8	35 3/8	192

