



Job Name: \_\_\_\_\_

Job Location: \_\_\_\_\_

Contractor: \_\_\_\_\_

Engineer: \_\_\_\_\_

Approval: \_\_\_\_\_

# Silver King® Number 5 Hydronic Cleaner

## Design Features:

- With Silicon SK-24
- Prevents Formulation of Insulating Scale on Heat Transfer Surfaces
- Keeps Dissolved Solids in Solution
- Frees and Lubricates Stuck Zone Values
- Dissolves Insulating Sludge on Tankless Coils
- Prevents Corrosion Protects and Lubricates Pump Seals
- Quiets Noisy Circulators
- Insures Maximum Heat Transfer Safe to use in all Boilers
- Contains no Petroleum or Hazardous Components
- Compatible with Both Ethylene Glycol and Propylene Glycol Antifreeze



**Use:** Hydronic Formula #5 is scientifically formulated to clean and protect boilers and hydronic heating systems. Patented Hydronic #5 will maximize heating efficiency and prolong the useful life of the system.

**Instructions:** Shut boiler down, valve off system, remove pressure relief valve. Pour hydronic #5 into opening, replace valve, open lines, then fire boiler normally. To complete job without shutting system down, mix HYDRONIC #5 in a pail with water, inject directly into boiler draw-off with a SILVER KING ALL BRASS FORCE AND SUCTION PUMP.

W-R#	Description	Weight	Min	Box
1025004	1 quart	2.30 lbs.	1	12

*Use one quart for each 110,000 BTU's of boiler rating.  
Use 1 qt. for every 30 gallons of system water*

**For best results, use once a year.**