XIRTEC PRESSURE PIPE

Dimension		PRODUCT CODE							
inches	mm	PVC Sch 40 White Plain End	PVC Sch 40 White Bell End	PVC Sch 40 Grey Bell End	PVC Sch 80 Grey Plain End	PVC Sch 80 Grey Bell End	CPVC Sch 40 Plain End	CPVC Sch 80 Plain End	CPVC Sch 80 Bell End
1/2 x 10'	12 x 3m	022600	022603	022004	–	085106	–	–	–
3/4 x 10'	20 x 3m	022633	022604	022011	–	085111	–	–	–
1 x 10'	25 x 3m	022612	022611	022016	–	085114	–	–	–
1-1/4 x 10'	32 x 3m	022608	022674	022027	–	085119	–	–	–
1-1/2 x 10'	40 x 3m	022614	022616	022032	–	–	–	–	–
2 x 10'	50 x 3m	022618	022619	022037	–	–	–	–	–
2-1/2 x 10'	65 x 3m	022621	–	022042	–	–	–	–	–
3 x 10'	75 x 3m	022637	022624	022046	–	–	–	–	–
4 x 10'	100 x 3m	022626	022628	–	085138	–	–	–	–
6 x 10'	150 x 3m	022666	022659	–	085143	–	–	–	–
1/4 x 20'	6 x 6m	–	–	–	085103	–	–	–	–
3/8 x 20'	10 x 6m	–	–	–	085104	–	–	–	–
1/2 x 20'	12 x 6m	022602	022601	–	085101	085108	019300	019203	–
3/4 x 20'	20 x 6m	022677	022607	–	085107	085112	019301	019205	–
1 x 20'	25 x 6m	022606	022610	–	085110	085116	019302	019207	–
1-1/4 x 20'	32 x 6m	022678	022617	–	085117	085122	019303	019209	–
1-1/2 x 20'	40 x 6m	022675	022615	–	085115	085127	019304	019211	–
2 x 20'	50 x 6m	022679	022620	–	085120	085132	019305	019213	–
2-1/2 x 20'	65 x 6m	022646	022625	–	085125	085134	019306	019216	–
3 x 20'	75 x 6m	022623	022630	–	085130	085137	019307	019217	–
4 x 20'	100 x 6m	022627	022640	022040	085140	085139	019308	019219	–
5 x 20'	125 x 6m	022651	022650	–	085150	–	–	–	–
6 x 20'	150 x 6m	022665	022660	022060	085160	085162	019309	019220	019218
8 x 20'	200 x 6m	022681	022680	022058	085180	085147	019310	019221	019255
10 x 20'	250 x 6m	022691	222690	022061	085190	085192	019013	019222	–
12 x 20'	300 x 6m	022693	022692	022064	085195	085151	019016	019223	–
14 x 20'	350 x 6m	022682	022694	–	085158	085152	–	019228	–
16 x 20'	400 x 6m	022683	022696	–	085153	085155	019226	019229	–
18 x 20'	450 x 6m	022687	022697	–	085159	–	–	–	–
20 x 20'	500 x 6m	022702	022698	–	–	085170	–	–	–
24 x 20'	600 x 6m	022704	022699	–	–	085171	–	–	–

FOR XIRTEC PVC SCHEDULE 40 WHITE

† Fabricated fittings

▮ Molded fittings: 150 psi max. working pressure, non-shock @ 23°C (73°F)

FOR XIRTEC PVC SCHEDULE 40 GREY

† Indicates fabricated and fiberglass reinforced pipe fittings

◗ Indicates Series 160 Fabricated and Fiberglass reinforced pipe fittings. The maximum continuous working pressure of fittings is 160 psi @ 23°C (73°F) under ideal conditions. no provisions have been made for pressure surges, water hammer, or other conditions which should be considered.