

PERFECT PITCH®

SAVE TIME INSTALLING CONDENSATE DRAINS



Position **Stanchions** at maximum 4 foot intervals to conform with AC manufacturer's instructions as well as all applicable codes.



Ensures an accurate, code-compliant pitch on condensate and waste drain pipe installations

FOR USE WITH • Air Handlers • Gas Furnaces • Gas Boilers • Hot Water Heaters • Condensate/Waste Applications

THE PROBLEM



WATER DAMAGE, the 2nd most frequently filed insurance claim, **IS OFTEN CAUSED BY IMPROPERLY PITCHED DRAIN LINES.**



Improper pitch as a result of using scrap materials during installation can lead to liquid and bacterial build-up, causing cracks in drain pipe over time.

THE SOLUTION



Perfect Pitch® is an adjustable fastening system that simplifies condensate and waste piping installations by providing an easy-to-use calibrated fixture for clean, professional-looking and code-compliant installations. This award-winning product saves time and labor, and ensures Perfect Pitch® for peace of mind.

FEATURES



Pipe Versatility

Fits almost any diameter run. Attach any style 1/2", 3/4", 1", 2" and 3" pipe. Works for PVC, CPVC, ABS or copper pipe.



Angled Slot Base

Screw slots on base are angled to accommodate clearance for drill chuck.



Built-in Ruler

Set pitch to desired intervals using built-in ruler. Measure vertically up to 16".



Stackable Design

Stack stanchions for longer runs and more complex installations.



Multiple Lines

Run parallel or multiple pipes on one stanchion, increase space efficiency on intricate installations.



Lock Into Place

Using solid glass filled material, molded teeth keep clamps and attachments from slipping or sagging.

THE SYSTEM



PPK-START

Starter Kit

Includes **5 Stanchions** and **5 Universal Pipe Clamps** to fit 1/2", 3/4" or 1" diameter.



PPA-UCS

1" Pipe and Under 2" Pipe and Over

Use the **Universal Pipe Clamp** attachment for diameters of 1/2", 3/4" and 1". Determine pitch necessary and snap the Clamp into the Stanchion.

2" Pipe and Over

Use the **Universal Pipe Clamp Adaptor** for large diameter pipes provides stability in heavier installations, such as gas furnace condensate. The **2" Clamp** and the **3" Clamp** snap into dovetails on Clamp Adaptor.



PPA-CAD4



2" Clamp PPA-2C4



3" Clamp PPA-3C4

QUICK SPECS

Test	Result	Method
Weight Limit	35 lb Max	N/A
Tensile Strength	6,500 psi	ASTM D 638
Gardner Impact	6 in-lbs	ASTM D5420
Deflection Temperature @66psi	300° F	ASTM D648