

## 3U Rack Mount Series



Output Pressure Range	Supply Voltage Max Amp Draw	Remote Monitoring & Connector	Part Number
0.5 - 10psig	115VAC 2.1 at 60hz	None	WDH2-3U-10-120
		Ethernet - RJ45	WDH2-3U-10-120-ERM
		Voltage (0-10VDC) 3wire M12, w/ 1m cable flying leads	WDH2-3U-10-120-OPM15V
		Current (4-20mA) 3wire M12, w/1m cable flying leads	WDH2-3U-10-120-OPM15C
	220/230VAC 1.0 at 60hz 1.3 at 50hz	None	WDH2-3U-10-240
		Ethernet	WDH2-3U-10-240-ERM
		Voltage (0-10VDC) 3wire M12, w/ 1m cable flying leads	WDH2-3U-10-240-OPM15V
		Current (4-20mA) 3wire M12, w/ 1m cable flying leads	WDH2-3U-10-240-OPM15C

<b>Enclosure</b>	Dimensions: Weight: Mounting:	17.625" x 15.25" x 5.25" (448 mm x 387 mm x 133 mm) 24 lbs (11.3 kg) Dual-post rack, flush mounted
<b>Power</b>	Power usage: Compressor type:	483 VA max Oil-less reciprocating diaphragm, 1/16 HP motor,
<b>Output</b>	Flow rate: Pressure rating: Factory default pressure setting: Output Port:  Dewpoint:	.5 cfm @ 1 psig Regulated = 0.5 - 10 psig 1 psig 1/4" NPT 3/8" or 1/4" OD push to connect fittings (1 each included) 0° to -20°F
<b>Environmental</b>	Temperature rating: Noise Level:	40° to 104°F < 70 dB(A)