



Compact cylinder ADN-100-60-I-P-A

Part number: 536391

FESTO

Per ISO 21287, with position sensing and internal piston rod thread



Data sheet

| Feature | values |
|--|--|
| Stroke | 60 mm |
| Piston diameter | 100 mm |
| Piston rod thread | M12 |
| Cushioning | P: Flexible cushioning rings/plates at both ends |
| Assembly position | Any |
| Conforms to standard | ISO 21287 |
| Piston-rod end | Female thread |
| Position detection | For proximity sensor |
| Variants | Single-ended piston rod |
| Working pressure | 0.6 ... 10 bar |
| Mode of operation | double-acting |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC | 2 |
| Ambient temperature | -20 ... 80 °C |
| Impact energy in end positions | 2.5 J |
| Theoretical force at 6 bar, return stroke | 4,524 N |
| Theoretical force at 6 bar, advance stroke | 4,712 N |
| Moving mass with 0 mm stroke | 570 g |
| Additional weight per 10 mm stroke | 98 g |
| Basic weight for 0 mm stroke | 2,154 g |
| Additional mass factor per 10 mm of stroke | 25 g |
| Mounting type | Optional with through hole with internal (female) thread with accessories |
| Pneumatic connection | G1/8 |
| Materials note | Conforms to RoHS |
| Materials information for cover | Aluminum die cast coated |
| Materials information for seals | TPE-U(PUR) |
| Materials information for piston rod | High alloy steel |
| Materials information for cylinder barrel | Wrought Aluminum alloy Smooth anodized |