


Push-in fitting CRQS-M5-6-I

Part number: 132329

FESTO

male thread with internal hexagon socket.



Data sheet

Feature	values
Size	Standard
Nominal size	2 mm
Type of seal on screw-in stud	Sealing ring
Assembly position	Any
Container size	1
Design structure	Push/pull principle
Operating pressure complete temperature range	-0.95 ... 10 bar
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:-:-] Water as per manufacturer's declaration at www.festo.com
Note on operating and pilot medium	Lubricated operation possible
Corrosion resistance classification CRC	4
Food-safe	See Supplementary material information
Ambient temperature	-15 ... 120 °C
Authorization	Germanischer Lloyd
Nominal tightening torque	1.33 Nm
Tolerance for nominal tightening torque	± 20 %
Product weight	7.7 g
Usable wires	PFAN
Pneumatic connection, port 1	Male thread M5
Pneumatic connection, port 2	for tubing, 6mm outside diameter
Materials note	Conforms to RoHS
Materials information, housing	High alloy steel, non-corrosive
Release ring material data	High alloy steel, non-corrosive
Materials information for tubing seal	FPM
Hose clamping segment material data	High alloy steel, non-corrosive