


# Push-in/threaded L-fitting CRQSL-1/8-1/4-U

Part number: 565327

FESTO



## Data sheet

| Feature                                       | values                                                   |
|-----------------------------------------------|----------------------------------------------------------|
| Size                                          | Standard                                                 |
| Nominal size                                  | 0.217 "                                                  |
| Assembly position                             | Any                                                      |
| Container size                                | 1                                                        |
| Design structure                              | Push/pull principle                                      |
| Operating pressure complete temperature range | -13.8 ... 203.1 Psi                                      |
| Operating medium                              | Compressed air in accordance with ISO8573-1:2010 [7:-:-] |
| Corrosion resistance classification CRC       | 4                                                        |
| Ambient temperature                           | -4 ... 302 °F                                            |
| Max. tightening torque                        | 8.851 ft-lbf                                             |
| Product weight                                | 0.705 oz                                                 |
| Usable wires                                  | PFAN                                                     |
| Pneumatic connection, port 1                  | Male thread NPTF1/8-27                                   |
| Pneumatic connection, port 2                  | for tubing, 1/4" outside diameter                        |
| Materials note                                | Contains PWIS substances<br>Conforms to RoHS             |
| Materials information, housing                | High alloy steel, non-corrosive                          |
| Release ring material data                    | High alloy steel, non-corrosive                          |
| Materials information for tubing seal         | FPM                                                      |
| Hose clamping segment material data           | High alloy steel, non-corrosive                          |