



# Round cylinder DSNU-63-250-P-A

Part number: 196018

**FESTO**

For position sensing, with elastic cushioning rings in end positions.  
Various mounting options, with or without additional mounting components.



## Data sheet

| Feature                                    | values                                                                      |
|--------------------------------------------|-----------------------------------------------------------------------------|
| Stroke                                     | 250 mm                                                                      |
| Piston diameter                            | 63 mm                                                                       |
| Piston rod thread                          | M16x1,5                                                                     |
| Cushioning                                 | P: Flexible cushioning rings/plates at both ends                            |
| Assembly position                          | Any                                                                         |
| Design structure                           | Piston<br>Piston rod<br>Cylinder barrel                                     |
| Position detection                         | For proximity sensor                                                        |
| Working pressure                           | 1 ... 10 bar                                                                |
| Mode of operation                          | double-acting                                                               |
| Operating medium                           | Compressed air in accordance with ISO8573-1:2010 [7:4:4]                    |
| Note on operating and pilot medium         | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC    | 2                                                                           |
| Ambient temperature                        | -20 ... 80 °C                                                               |
| Theoretical force at 6 bar, return stroke  | 1,681.9 N                                                                   |
| Theoretical force at 6 bar, advance stroke | 1,870.3 N                                                                   |
| Moving mass                                | 1,084 g                                                                     |
| Product weight                             | 2,545 g                                                                     |
| Mounting type                              | with accessories                                                            |
| Pneumatic connection                       | G3/8                                                                        |
| Materials note                             | Conforms to RoHS                                                            |
| Materials information for cover            | Wrought Aluminum alloy                                                      |
| Materials information for seals            | NBR<br>TPE-U(PU)                                                            |
| Materials information for piston rod       | High alloy steel                                                            |
| Materials information for cylinder barrel  | High alloy steel, non-corrosive                                             |