


One-way flow control valve GRLA-M5-PK-3-B

Part number: 151161

FESTO



Data sheet

Feature	values
Valve function	One-way flow control function for exhaust air
Pneumatic connection, port 1	PK-3
Pneumatic connection, port 2	M5
Adjusting element	Slotted head screw
Mounting type	Threaded
Standard nominal flow rate in flow control direction	83 l/min
Standard nominal flow rate in non-return direction	72 ... 83 l/min
Working pressure	0.2 ... 10 bar
Ambient temperature	-10 ... 60 °C
Authorization	Germanischer Lloyd
Assembly position	Any
Standard flow rate in direction of flow control: 6 -> 0 bar	140 l/min
Standard flow rate in blocked direction: 6 -> 0 bar	120 ... 140 l/min
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Medium temperature	-10 ... 60 °C
Nominal size	2 mm
Max. tightening torque	1.5 Nm
Product weight	10 g
Materials information for screw-in stud	Nickel plated
Materials note	Conforms to RoHS
Materials information for seals	NBR
Regulating screw material data	Brass
Swivel joint material data	Zinc die-casting