



Parallel gripper HGPM-12-EZ-G6

Part number: 197568

FESTO

Micro, stroke compensation.



Data sheet

Feature	values
Size	12
Stroke per gripper jaw	3 mm
Max. replacement accuracy	0.2 mm
Repetition accuracy, gripper	≤ 0.05 mm
Number of gripper fingers	2
Mode of operation	single-acting closed
Gripper function	Parallel
Design structure	Inclined plane
Position detection	No
Total force at 6 bar, closing	35 N
Working pressure	4 ... 8 bar
Max. operating frequency of gripper	4 Hz
Min. opening time at 6 bar	3 ms
Min. closing time at 6 bar	8.3 ms
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Corrosion resistance classification CRC	1
Ambient temperature	5 ... 60 °C
Spring force of stroke compensator	10 ... 23 N
Gripping force per gripper jaw at 6 bar, opening	17.5 N
Max. force on gripper jaw Fz static	30 N
Max. torque at gripper Mx static	0.5 Nm
Max. torque at gripper My static	0.5 Nm
Max. torque at gripper Mz static	0.5 Nm
Product weight	62 g
Mounting type	with through hole
Pneumatic connection	M3
Materials note	Free of copper and PTFE
Materials information for cover cap	POM
Materials information, housing	Wrought Aluminum alloy Anodized
Materials information for gripper jaws	High alloy steel