



Angle gripper HGWM-08-EO-G6

Part number: 185693

FESTO

Micro, stroke compensation.



Data sheet

Feature	values
Size	8
Max. angular gripper jaw backlash ax,ay	0.5 deg
Max. gripper jaw backlash Sz	0.03 mm
Max. opening angle	17 deg
Repetition accuracy, gripper	≤ 0.02 mm
Number of gripper fingers	2
Mode of operation	single-acting open
Gripper function	Angle
Design structure	Inclined plane
Position detection	No
Working pressure	2 ... 8 bar
Max. operating frequency of gripper	4 Hz
Min. opening time at 6 bar	2.7 ms
Min. closing time at 6 bar	1.2 ms
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:-:-]
Corrosion resistance classification CRC	2
Ambient temperature	5 ... 60 °C
Spring force of stroke compensator	4 ... 6 N
Spring return moment	0.5 Ncm
Total gripping torque at 6 bar, closing	22 Ncm
Max. force on gripper jaw Fz static	7 N
Max. torque at gripper Mx static	20 Ncm
Max. torque at gripper My static	20 Ncm
Max. torque at gripper Mz static	20 Ncm
Product weight	23 g
Mounting type	with internal (female) thread
Pneumatic connection	M3
Materials note	Free of copper and PTFE
Materials information for cover cap	POM
Materials information, housing	High alloy steel, non-corrosive
Materials information for gripper jaws	High alloy steel