
Fine filter
LFMB-3/8-D-MIDI

Part number: 162629

With 1 µm filter cartridge, metal bowl guard.





Data sheet

Feature	values
Series	D
Size	Midi
Design structure	Fiber filter
Grade of filtration	1 µm
Condensate drain	manual rotary
Working pressure	1 ... 16 bar
Operating medium	Compressed air in accordance with ISO8573-1:2010 [6:8:4] Inert gases
Air purity class at output	Compressed air to ISO 8573-1:2010 [5:7:3] Inert gases
Max. standard flow rate for air quality class	1,420 l/min
Min. standard flow rate for air quality class	500 l/min
Filter efficiency	99.99 %
Max. condensate volume	43 cm3
Bowl guard	Metal bowl guard
Corrosion resistance classification CRC	2
Medium temperature	1.5 ... 60 °C
Ambient temperature	-10 ... 60 °C
Storage temperature	-10 ... 60 °C
Residual oil content	0.5 mg/m3
Mounting type	Optional Line installation with accessories
Assembly position	Vertical +/- 5°
Pneumatic connection, port 1	G3/8
Pneumatic connection, port 2	G3/8
Materials information, housing	Zinc die-casting
Materials information for filter	Boron silicate fiber
Materials information for bowl	PC
Materials note	Free of copper and PTFE Conforms to RoHS
Product weight	650 g