# Filter regulator
# LFR-1/2-D-5M-O-MIDI-A

Part number: 192625

With metal bowl guard without pressure gauge, degree of filtration 5 µm. With automatic condensate drain.






## Data sheet

| Feature | values |
|---|---|
| Size | Midi |
| Series | D |
| Actuator lock | Rotary knob with lock |
| Assembly position | Vertical +/- 5° |
| Grade of filtration | 5 µm |
| Condensate drain | fully automatic |
| Design structure | Filter regulator without pressure gauge |
| Max. condensate volume | 43 cm3 |
| Bowl guard | Metal bowl guard |
| Pressure gauge | Prepared for G1/4 |
| Working pressure | 2 ... 12 bar |
| Pressure regulation range | 0.5 ... 12 bar |
| Max. pressure hysteresis | 0.2 bar |
| Standard nominal flow rate | 2,600 l/min |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:9:-]<br>Inert gases |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC | 2 |
| Storage temperature | -10 ... 60 °C |
| Air purity class at output | Compressed air in accordance with ISO8573-1:2010 [6:8:4]<br>Inert gases |
| Medium temperature | 5 ... 60 °C |
| Ambient temperature | 5 ... 60 °C |
| Authorization | Germanischer Lloyd |
| Product weight | 900 g |
| Mounting type | Optional<br>Line installation<br>with accessories |
| Pneumatic connection, port 1 | G1/2 |
| Pneumatic connection, port 2 | G1/2 |
| Materials note | Free of copper and PTFE<br>Conforms to RoHS |
| Materials information, housing | Zinc die-casting |
| Materials information for bowl | PC |