

# Lubricator
# LOE-D-MAXI-U

Part number: 546517

Without threaded connection plates with FRB threaded pin, with metal bowl guard.





## Data sheet

| Feature | values |
|---|---|
| Size | Maxi |
| Series | D |
| Assembly position | Vertical +/- 5° |
| Design structure | proportional standard mist lubricator |
| Max. oil capacity | 6.46 oz(l) |
| Bowl guard | Metal bowl guard |
| Working pressure | 0 ... 240 Psi |
| Minimum flow rate for lubricator function | 0.35 cfm |
| Standard nominal flow rate | 294 cfm |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4]<br>Inert gases |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC | 2 |
| Storage temperature | 14 ... 140 °F |
| Air purity class at output | Compressed air in accordance with ISO8573-1:2010 [7:4:-]<br>Inert gases |
| Medium temperature | 14 ... 140 °F |
| Ambient temperature | 14 ... 140 °F |
| Authorization | Germanischer Lloyd |
| Product weight | 42 oz |
| Mounting type | with accessories |
| Materials note | Conforms to RoHS |
| Materials information for bowl | PC |