
Filter regulator MS4-LFR-1/4-D7-EUM-AS Part number: 535724

★ Core product range

12 bar maximum output pressure, 40 µm filter, with pressure gauge, lockable regulator head, metal bowl, manual condensate drain, direction of flow: from left to right.







Data sheet

Feature	values
Size	4
Series	MS
Actuator lock	Rotary knob with lock
	with accessories, lockable
Assembly position	Vertical +/- 5°
Grade of filtration	40 μm
Condensate drain	manual rotary
Design structure	Filter regulator with pressure gauge
Max. condensate volume	25 ml
Controller function	Output pressure constant
	with secondary exhaust
	with return flow
Bowl guard	integrated as metal shell
Pressure gauge	with pressure gauge
Working pressure	0.8 14 bar
Pressure regulation range	0.5 12 bar
Max. pressure hysteresis	0.25 bar
Standard nominal flow rate	1,500 l/min
Operating medium	Compressed air to ISO 8573-1:2010 [-:4:-]
	Inert gases
Corrosion resistance classification CRC	2
Storage temperature	-10 60 °C
Air purity class at output	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Medium temperature	-10 60 °C
Ambient temperature	-10 60 °C
Product weight	475 g
Mounting type	Optional
	Front panel installation
	Line installation
	with accessories
Pneumatic connection, port 1	G1/4
Pneumatic connection, port 2	G1/4
Materials note	Conforms to RoHS
Materials information for subbase	Aluminum die cast
Materials information for control panel	POM
	PA
Materials information for seals	NBR
Materials information for filter	PE
Materials information, housing	Aluminum die cast
Materials information for membrane	NBR
Materials information for bowl	Aluminum die cast
	Wrought Aluminum alloy
Materials info, viewing window	PA
Material information, isolating disc	POM