



Lubricator MS6-LOE-1/4-U

Part number: 529781

FESTO

Metal bowl, direction of flow: from left to right.



Data sheet

| Feature | values |
|---|---|
| Size | 6 |
| Series | MS |
| Assembly position | Vertical +/- 5° |
| Design structure | proportional standard mist lubricator |
| Max. oil capacity | 80 cm ³ |
| Bowl guard | integrated as metal shell |
| Working pressure | 1 ... 16 bar |
| Minimum flow rate for lubricator function | 50 l/min |
| Standard nominal flow rate | 2,500 l/min |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] Inert gases |
| Note on operating and pilot medium | Lubricated operation possible |
| Corrosion resistance classification CRC | 2 |
| Storage temperature | -10 ... 60 °C |
| Medium temperature | 0 ... 60 °C |
| Oil viscosity | ISO VG 32 |
| Ambient temperature | 0 ... 60 °C |
| Product weight | 810 g |
| Mounting type | Optional Line installation with accessories |
| Pneumatic connection, port 1 | G1/4 |
| Pneumatic connection, port 2 | G1/4 |
| Materials note | Conforms to RoHS |
| Materials information, housing | Aluminum die cast |
| Materials information for bowl | Wrought Aluminum alloy |