


SPECIFICATIONS			
CONTACT CARRIER MATERIAL	NYLON OR TPU		
MOLDED HEAD MATERIAL/COLOR	TPU/YELLOW		
CONTACT MATERIAL/PLATING	BRASS/GOLD		
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL		
RATED CURRENT [A]	2.0 A		
RATED VOLTAGE [V]	125 VAC/VDC		
OUTER JACKET MATERIAL/COLOR	PVC/YELLOW		
CONDUCTOR INSULATION MATERIAL	PVC		
NUMBER OF CONDUCTORS [AWG]	4x26 AWG		
TEMPERATURE RANGE	-40°C to +105°C (-40°F to +221°F)		
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67		

SOURCE DRAWING - FOR REFERENCE ONLY



CABLE LENGTH	TOLERANCE *					
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER					
STRIP LENGTH	TOLERANCE *					
0-7mm	±0.5mm					
8-29mm	±1.0mm					
30-49mm	±2.0mm					
50-69mm	±3.0mm					
70-100mm	±4.0mm					
OVER 100mm	±5.0mm					
* UNLESS OTHERWISE SPECIFIED						

## NOTES:

REV DESCRIPTION

1. "\*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

E DRAWING PROCESSED AS PART OF ECO 33971

$\dashv$										
				RELATED DOCUMENTS  1.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK		ick iac	3000 CAMPU MINNEAPOLIS,	MN 55441
J			<ol> <li>3.</li> <li>4.</li> </ol>	⊕ □	INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	High Technology Sensors and Automation Controls		(763) 553- (763) 553-	1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com	
CK TO URDER			DISPLAY DRAWIN REFER!	ALL DIMENSIONS DISPLAYED ON THIS	DRFT CBM	DATE 04/28/99	DESCRIPTION PKG 4M-*			
					DSGN	SCALE 1=1.0	T NG	4101-		
				DRAWING ARE FOR REFERENCE ONLY	UNIT OF MEASUREMENT		IDENTIFICATION NO.		REV	
				CONTACT TURCK FOR MORE	MILLIMETER [ INCH ]				l F	
	СВМ	04/06/11	33971		INFORMATION					
	BY	DATE	ECO NO.			DO NOT SCALE	THIS DRAWING	FILE: 777000280	SHE	ET 1 OF 1