Suction cup F110 Silicone, G1/2" female, with **piab** cone valve, 0101914





- Suitable for flat objects.
- Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.

General

Curve radius	250 mm
Movement, vertical max.	4 mm
Application	Dry sheet metal
Material	Silicone (SIL)
Suction cup model	F
Suction cup shape	Flat
Volume	70 cm ³
Weight	66 g

Fitting

Fitting size	1/2"
Fitting style	Female
Fitting type	G-thread
Fitting option	Cone valve

Dimension

Height	61.6 mm
Outer diameter	112 mm

Performance — lifting forces

	<u> </u>	1	
20 -kPa	140 N	140 N	
60 -kPa	420 N	250 N	
90 -kPa	560 N	300 N	


Material

	Silicone (SIL)
Colour	Red
Hardness	50 'Shore A
Temperature	-40 − 200 °C

Material resistance

	Silicone (SIL)
Alcohol	**
Concentrated acids	-
Ethanol	N/A
Hydrolysis	•
Methanol	N/A
Oil	-
Oxidation	***
Petrol	-
Wear resistance	**
Weather and ozone	***

Dimensional drawings



Spare parts

	Item no.
Suction cup F110 Silicone	3150132S
Fitting 110, G1/2" female, with cone valve	0100563
Cone valve for Fitting 110 & 150	3350034

Accessories

	Item no.
Suction cup F110 Nitrile-PVC with washer	3150038P
Suction cup F110 Silicone with washer	3150038S
Suction cup F110 HNBR with washer	3150038T
Suction cup F110 Nitrile-PVC	3150132P
Suction cup F110 HNBR	3150132T
Fitting 110 G3/8" female, with mesh filter	0100557
Fitting 110, 3/8" NPSF female, with mesh filter	0100559
Fitting 110, G1/2" female, with mesh filter	0100561
Fitting G1/2" female Al, with mesh filter	3250007