Suction cup F110 Silicone FCM, 0200302





- The silicone material complies with FDA 21 CFR 177.2600 & EU 1935/2004.
- Suitable for flat objects.
- Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.

General

Curve radius	250 mm
Movement, vertical max.	4 mm
Application	Food contact materials (FDA & EU), non-detectable
Material	Silicone (SIL FDA)
Suction cup model	F
Suction cup shape	Flat
Volume	70 cm ³
Weight	66 g

Fitting

Fitting size	None	
·g		
Fitting style	None	
i itting styte	None	
Fitting tupo	None	
Fitting type	None	
Fitting option	None	

Dimension

Height	20 mm
Outer diameter	112 mm

Performance — lifting forces

	±	_
20 -kPa	140 N	140 N
60 -kPa	420 N	250 N
90 -kPa	560 N	300 N


Material

	Silicone (SIL FDA)
Colour	Transparent
Hardness	50 'Shore A
Temperature	-40 – 200 °C

Material resistance

	Silicone (SIL FDA)
Alcohol	**
Concentrated acids	-
Ethanol	N/A
Hydrolysis	•
Methanol	N/A
Oil	-
Oxidation	***
Petrol	-
Wear resistance	**
Weather and ozone	***

Dimensional drawings



Accessories

	Item no.
Fitting 110, G1/2" female, with mesh filter	0100561
Fitting 110, 3/8" NPSF female, with mesh filter	0100559