# Suction cup F15 Silicone FCM, M5 male, 9909623





- The silicone material complies with FDA 21 CFR 177.2600 & EU 1935/2004.
- Suitable for flat objects.
- Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.
- Cleats prevent thin, sensitive objects from being deformed and gives extra friction when the lifting force is parallel.

#### General

Curve radius	13 mm
Movement, vertical max.	1 mm
Application	Food contact materials (FDA & EU), non-detectable
Material	Silicone (SIL FDA)
Suction cup model	F
Suction cup shape	Flat
Volume	0.37 cm <sup>3</sup>
Weight	0.9 g

### **Fitting**

Fitting size	None
Fitting style	Male
Fitting type	M-thread
Fitting option	None

#### **Dimension**

Height	19.5 mm	
Outer diameter	15.7 mm	

## Performance — lifting forces

	<b>±</b>	<b>±</b>
20 -kPa	3.5 N	3.5 N
60 -kPa	8.5 N	6.5 N
90 -kPa	11 N	7.5 N


#### **Material**

	Silicone (SIL FDA)
Colour	Transparent
Hardness	50 'Shore A
Temperature	-40 – 200 °C

## Material resistance

	Silicone (SIL FDA)
Alcohol	**
Concentrated acids	-
Ethanol	N/A
Hydrolysis	•
Methanol	N/A
Oil	-
Oxidation	***
Petrol	-
Wear resistance	++
Weather and ozone	***

## Dimensional drawings



## Spare parts

	Item no.
Fitting M5 male, 10-15	3107030
Suction cup F15 Silicone FCM	0200263