

# Suction cup F15MF Thermoelastic polyurethane, M5 male, 3250074



- Suction cup of TPU, a mark free material that leaves no trace on the object being handled.
- Suitable for flat surfaces.
- Good stability and little inherent movement.
- Recommended when the lifting force is parallel to the surface of the object.

## General

Curve radius	17 mm
Movement, vertical max.	1 mm
Application	Mark Free
Material	Thermoplastic Polyurethane (TPE-U)
Suction cup model	F-MF
Suction cup shape	Flat
Volume	0.37 cm <sup>3</sup>
Weight	0.8 g

## Fitting

Fitting size	M5
Fitting style	Male
Fitting type	M-thread
Fitting option	None

## Dimension

Height	19.5 mm
Outer diameter	16.5 mm

## Performance — lifting forces

		
20 -kPa	4 N	4.5 N
60 -kPa	8 N	9 N
90 -kPa	12 N	14.5 N


## Material

	Thermoplastic Polyurethane (TPE-U)
Colour	White transparent
Hardness	81 °Shore A
Temperature	-20 – 80 °C

## Material resistance

	Thermoplastic Polyurethane (TPE-U)
Alcohol	++
Concentrated acids	-
Ethanol	N/A
Hydrolysis	-
Methanol	N/A
Oil	+++
Oxidation	++
Petrol	-
Wear resistance	+++
Weather and ozone	+++

## Dimensional drawings



## Spare parts

	Item no.
Suction cup F15MF Thermoelastic polyurethane	3150269
Fitting M5 male, 10-15	3107030