


Push-in/threaded L-fitting, long QSMLLV-M7-4-I

Part number: 130836

FESTO

360° orientable, external thread with internal hexagon.



Data sheet

| Feature | values |
|---|--|
| Size | Mini |
| Nominal size | 1.9 mm |
| Type of seal on screw-in stud | Sealing ring |
| Assembly position | Any |
| Container size | 10 |
| Design structure | Push/pull principle |
| Operating pressure complete temperature range | -0.95 ... 6 bar |
| Temperature dependent working pressure | -0.95 ... 14 bar |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:-:-] |
| Note on operating and pilot medium | Lubricated operation possible |
| Corrosion resistance classification CRC | 1 |
| Ambient temperature | -10 ... 80 °C |
| Authorization | Germanischer Lloyd |
| Nominal tightening torque | 3.35 Nm |
| Tolerance for nominal tightening torque | ± 20 % |
| Product weight | 11.8 g |
| Pneumatic connection, port 1 | Male thread M7 |
| Pneumatic connection, port 2 | for tubing, 4mm outside diameter |
| color of release ring | blue |
| Materials note | Conforms to RoHS |
| Materials information, housing | PBT |
| Release ring material data | POM |
| Materials information for tubing seal | NBR |
| Hose clamping segment material data | High alloy steel, non-corrosive |