

# Multiple distributor

## QSQ-1/8-5/32-U

Part number: 153810

FESTO

360° orientable, 4 outlets.



## Data sheet

| Feature                                       | values                                                   |
|-----------------------------------------------|----------------------------------------------------------|
| Size                                          | Standard                                                 |
| Nominal size                                  | 2.6 mm                                                   |
| Type of seal on screw-in stud                 | coating                                                  |
| Assembly position                             | Any                                                      |
| Design structure                              | Push/pull principle                                      |
| Container size                                | 1                                                        |
| Operating pressure complete temperature range | -0.95 ... 10 bar                                         |
| Operating medium                              | Compressed air in accordance with ISO8573-1:2010 [7:-:-] |
| Note on operating and pilot medium            | Lubricated operation possible                            |
| Corrosion resistance classification CRC       | 1                                                        |
| Ambient temperature                           | -10 ... 60 °C                                            |
| Authorization                                 | Germanischer Lloyd                                       |
| Max. tightening torque                        | 8 Nm                                                     |
| Product weight                                | 20 g                                                     |
| Number of outputs                             | 4                                                        |
| Number of supply lines                        | 1                                                        |
| Pneumatic connection, port 1                  | Male thread NPT1/8-27                                    |
| Pneumatic connection, port 2                  | for tubing, 5/32" outside diameter                       |
| color of release ring                         | Grey                                                     |
| Materials note                                | Conforms to RoHS                                         |
| Materials information, housing                | PBT                                                      |
| Release ring material data                    | POM                                                      |
| Materials information for tubing seal         | NBR                                                      |
| Hose clamping segment material data           | High alloy steel, non-corrosive                          |