

10 and 12-Wire Receptacles, Front Mount, PG 9 Threads

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 60 VAC/75 VDC, 2 A



Housing Style	Female Part Number	Male Part Number	Features	Pinout	
<p>FK..*</p> <p>Typical panel cutout is 15.2 mm.</p>	FK 10-*	FS 10-*	10x24 AWG, 105°C, mates with 10-pin Cordsets	<p>Female</p> <p>Male</p>	<p>1. WH 2. BN 3. GN 4. YE 5. GY 6. PK 7. BU 8. RD 9. OG 10. TN</p>
<p>FS..*</p> <p>Typical panel cutout is 15.2 mm.</p>	FK 12-*	FS 12-*	12x24 AWG, 105°C, mates with 12-pin Cordsets	<p>Female</p> <p>Male</p>	<p>1. WH 2. BN 3. GN 4. YE 5. GY 6. PK 7. BU 8. RD 9. OG 10. TN 11. BK 12. VT</p>

* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.
Standard housing material is nickel plated brass "FS.."; "FSV.." indicates stainless steel.
To specify PVC jacketed cable, add "/S717" to the end of the part number.