


FEMALE END VIEW	TYPICAL PANEL CUTOUT
5 6 7 6 7 6 7 6 7 6 7 6 7 6 7 6 7 6 7 6	13.6 [0.54]



SPECIFICATIONS							
CONTACT CARRIER MATERIAL	NYLON OR TPU						
CONTACT MATERIAL/PLATING	BRASS/GOLD						
HOUSING/LOCKNUT MATERIAL/PLATING	BRASS/NICKEL						
RATED CURRENT [A]	1.5 A						
RATED VOLTAGE [V]	60 VAC/75 VDC						
NUMBER OF CONDUCTORS [AWG]	PRINTED CIRCUIT PINS						
TEMPERATURE RATING	-40°C TO +90°C (-40°F TO +194°F)						
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP68						
MAX. PANEL THICKNESS	3.0 [0.12]						





## SOURCE DRAWING - FOR REFERENCE ONLY

				RELATED DOCUMENTS  1. 2. 3. 4.	$\triangle \Box$	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	High Technology	3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com		
				MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR	DRFT RDS APVD	DATE 02/23/07 SCALE 1=1.0	DESCRIPTION FKFDK 8-	-PCB	
				FINISH	REFERENCE ONLY  CONTACT TURCK	Y UNIT OF MEASUREMENT		IDENTIFICATION NO. U2-116	ITIFICATION NO.  U2-11606	
 END VIEW OR UPDATE END VIEW TO SHOW APPROPRIATE ORIENTATION OF FLATS AND KEYWAY SCRIPTION	TV BY	02/03/16 DATE	53385 ECO NO.		FOR MORE INFORMATION	DO NOT SCALE	THIS DRAWING	FILE: U2-11606	SHI	EET 1 OF 1