


5-Wire Receptacles, Rear Mount, Reverse Key

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 250 V, 4 A



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p>FKFDW ..</p> <p>Typical panel cutout is 15.3 x 14.0 mm.</p>	FKFDW 4.5-*	FSFDW 4.5-*	5x22 AWG 105°C, mates with 5-pin <u>Reverse Key</u> <u>Cordset, leads, UL</u> Recognized, CSA Approved	<p>Female</p>
<p>FSFDW ..</p> <p>Typical panel cutout is 15.3 x 14.0 mm.</p>				
<p>FKFDLW ..</p> <p>Typical panel cutout is 15.3 x 14.0 mm.</p>	FKFDLW 4.5	FSFDLW 4.5	Accepts 20 AWG Max Leads, 105°C, mates with 5-pin <u>Reverse Key</u> <u>Cordset,</u> <u>solder cup</u>	<p>Male</p>
<p>FSFDLW ..</p> <p>Typical panel cutout is 15.3 x 14.0 mm.</p>				

Receptacles

* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.
Standard housing material is nickel plated brass.
To specify PVC jacketed cable, add "/S717" to the end of the part number.