



# Solenoid valve

## VUVG-L10A-P53E-ZT-M3-1P3

Part number: 566446

**FESTO**

This type is suitable for vacuum.



## Data sheet

Feature	values
Valve function	5/3 exhausted
Type of actuation	electrical
Valve size	10 mm
Standard nominal flow rate	90 l/min
Working pressure	-0.9 ... 10 bar
Design structure	Piston slide
Protection class	IP40 IP65 with plug socket
Authorization	RCM Mark c CSA us (OL) c UL us - Recognized (OL)
Nominal size	2 mm
Exhaust-air function	throttleable
Sealing principle	soft
Assembly position	Any
Manual override	detenting Pushing Covered
Type of piloting	Piloted
Pilot air supply	external
Note on forced dynamisation	Switching frequency at least once a week
Pilot pressure	3 ... 8 bar
Suitability for vacuum	Yes
Switching time off	25 ms
Switching time on	8 ms
Switching time reversal	14 ms
Duty cycle	100%
Characteristic coil data	24 V DC: 1 W 24 V DC: low-current phase 0.3 W, high-current phase 1.0 W
Permissible voltage fluctuation	+/- 10 %
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Restriction ambient and medium temperature	-5 - 50 °C Without holding current reduction
Corrosion resistance classification CRC	2
Medium temperature	-5 ... 60 °C
Pilot medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Ambient temperature	-5 ... 60 °C
Product weight	49 g
Electrical connection	Via electrical connection plate
Mounting type	Optional on manifold rail

Feature	values
	with through hole
Auxiliary pilot air port 12/14	M3
Pneumatic connection, port 1	M3
Pneumatic connection, port 2	M3
Pneumatic connection, port 3	M3
Pneumatic connection, port 4	M3
Pneumatic connection, port 5	M3
Materials note	Conforms to RoHS
Materials information for seals	HNBR NBR
Materials information, housing	Wrought Aluminum alloy