



# Solenoid valve

## VUVG-S14-M52-AZT-G18-1T1L

Part number: 573470

**FESTO**

This type is suitable for vacuum.



## Data sheet

| Feature                                 | values   |
|---|--|
| Valve function                          | 5/2 monostable   |
| Type of actuation                       | electrical   |
| Valve size                              | 14 mm  |
| Standard nominal flow rate              | 620 l/min  |
| Working pressure                        | -0.9 ... 10 bar  |
| Design structure                        | Piston slide   |
| Type of reset                           | Air spring   |
| Protection class                        | IP65<br>IP67   |
| Authorization                           | RCM Mark<br>c CSA us (OL)<br>c UL us - Recognized (OL)   |
| Exhaust-air function                    | throttleable   |
| Sealing principle                       | soft   |
| Assembly position                       | Any  |
| Manual override                         | detenting<br>Pushing   |
| Type of piloting                        | Piloted  |
| Pilot air supply                        | external   |
| Note on forced dynamisation             | Switching frequency at least once a week   |
| Signal status display                   | LED  |
| Pilot pressure                          | 2.5 ... 8 bar  |
| Max. switching frequency                | 3 Hz   |
| Switching time off                      | 26 ms  |
| Switching time on                       | 13 ms  |
| Duty cycle                              | 100%   |
| Max. positive test pulse with logic 0   | 1,600 µs   |
| Max. negative test pulse with logic 1   | 3,000 µs   |
| Characteristic coil data                | 22 V DC: 1 W   |
| Permissible voltage fluctuation         | +/- 10 %   |
| Operating medium                        | Compressed air in accordance with ISO8573-1:2010 [7:4:4]                                       |
| Note on operating and pilot medium      | Lubricated operation possible (subsequently required for further operation)                    |
| Vibration resistance                    | Transport application test at severity level 2 in accordance with FN 942017-4 and EN 60068-2-6 |
| Shock resistance                        | Shock test with severity level 2 in accordance with FN 942017-5 and EN 60068-2-27              |
| Corrosion resistance classification CRC | 2  |
| Medium temperature                      | -5 ... 60 °C   |
| Pilot medium                            | Compressed air in accordance with ISO8573-1:2010 [7:4:4]                                       |
| Ambient temperature                     | -5 ... 60 °C   |
| Product weight                          | 91 g   |
| Electrical connection                   | via manifold block   |
| Mounting type                           | on manifold rail   |
| Materials note                          | Conforms to RoHS   |
| Materials information for seals         | HNBR<br>NBR  |
| Materials information, housing          | Wrought Aluminum alloy   |