

LED LIGHT SOURCE PROJECTORS (2nd wave)

Whether you're looking for a projector with which to show movies to friends, an interactive model for a classroom, or a unit to make presentations in larger venues, we offer a variety of models for you to choose from. After FR-146 (a Full HD home theater projector), FR-179 (a XGA LED Mini Projector), FR-272 (a SVGA projector), FR-199 (PalmCute, a handheld super mini projector), FR-306 (an interactive model for classroom or conference room), we present our 2nd wave trendy LED LIGHT SOURCE PROJECTORS hereunder.

Smaller, thinner, and brighter are design themes of our 2nd wave LED light source projectors. They include a pocket-sized pico projector "POCKET30 (FR-317)", a slightly larger but much brighter palmtop model "PALM100 (FR-318)", and an even brighter mobile model "MOBILE200 (FR-319)". They are small, light, and easy to carry. You can use them to project digital images onto any nearby light color surface, such as a wall to view and share photos/movies/games with friends in a much pleasant way than force them to look at a tiny display on device such as a mobile phone. or at a small TV screen.



FR-317 POCKET30
Dimension: 122 x 69.5 x 13mm



FR-318 PALM100
Dimension: 143 x 89 x 27mm



FR-272B/C LCoS MOBILE
Dimension: 132 x 105 x 40mm



FR-319 MOBILE200
Dimension: 170 x 110 x 33mm

Model No.					
Specification		FR-317	FR-318	FR-319	FR-272B / FR-272C
Imaging technology		DLP	DLP	DLP	LCoS
Brightness		30 lumens	100 lumens	200 lumens	50 lumens
Resolution		640 X 480	854 X 480	1280 X 800	800 X 600
Light source		LED	LED	LED	LED
LED life		40,000 hours	40,000 hours	40,000 hours	40,000 hours
Projection size		6" ~ 92"	17" ~ 98"	17" ~ 98"	7" ~ 50"
Projection distance		0.2m ~ 3m	0.5m ~ 3m	0.5m ~ 3m	0.3m ~ 2m
Memory capacity		1GB	1GB	-	1GB
Video file format		MPEG1/2/4, H.264, M-JPEG, WMV3, RV3/4, DIVX	MPEG1/2/4, H.264, M-JPEG, WMV3, RV3/4, DIVX	MPEG1/2/4, RMVB/RM, MOV, MJPEG, DIVX	MPEG1/2/4, H.264, M-JPEG, WMV3, RV3/4, DIVX, WMA, OGG, AAC
Audio file format		MPEG1/2/3/4, WMA, OGG, AAC	MPEG1/2/3/4, WMA, OGG, AAC	WMA, MP3, AAC	MPEG1/2/3/4, WMA, OGG, AAC
Picture file format		JPG, JPEG, BMP	JPG, JPEG, BMP	JPEG, BMP, PNG	JPG, JPEG, BMP
USB Sub-Display		Support	Support	-	Support
Keystone correction		No	No	Yes	Yes
Input interface	USB HOST	No	Yes	Yes	Yes
	Mini USB	Yes	Yes	No	Yes
	VGA	No	No	Yes	No
	CVBS (RCA, AV)	Yes	Yes	Yes	Yes
Remote control		Yes	Yes	Yes	Yes
Audio output		Yes	Yes	Yes	Yes
Power supply		DC 5V/2A	DC 12V/2A	DC 20V/3A	DC 12V/1.25A
Rechargeable Lithium Battery		3.7V, 1200mAh	7.4V, 1200mAh	No	7.4V, 2200mAh (for FR-272B)
World/Excel files readable		Yes	Yes	No	Yes
Dimension		122 X 69.5 X 13 (mm)	143 X 89 X 27 (mm)	170 X 110 X 33 (mm)	132 X 105 X 40 (mm)

(Note: Specifications subject to change without notice.)

Ultmost / **FUSS** / **OVO** Manufacturer & Exporter Since 1987

Ultmost Technology Group - China Operation

World Electronic (Shenzhen) Co., Ltd.

Add.: No.160, Longping West Rd, Longgang District, Shenzhen City, Guangdong, China (Zip Code: 518172)

Tel: 86-755-61292888 (Rep.), Fax: 86-755-61292988 (Rep.), E-mail: ut@ultmost.com.cn

Sales Direct Lines: 86-755-84880719 (Tel.) / 86-755-84880780 (Tel.) / 86-755-84820817 (Fax)

<http://www.fussdigital.com>(for IT & Digital Entertainment) <http://www.fussdigital.com/ovo/>(for Digital photo Frame) <http://www.ultmost.com>(for Small Gadgets)