

1		2		3		4		5		6			
REV.	REMARK			DATE	SIGN.								
I	WIRING DIAGRAM											I	
H	MINI SAS 4X (P0)			SAS DRIVE CABLE REC.				4P POWER PLUG					
	PIN	SIGNAL	REC.	PIN	SIGNAL	PLUG	PIN	SIGNAL					
	A2	RX0+	P1	S6	TP+	P5							
	A3	RX0-		S5	TP-								
	B3	TX0-		S3	RP-								
	B2	TX0+		S2	RP+								
	GND GROUP	GND		S1,S4,S7	GND								
				P13,P14,P15	+12V		1	+12V					
				P10,11,12	GND		2	GND					
	G				P7,P8,P9	+5V	4	+5V					
				P4,P5,P6	GND	3	GND						
A5		RX1+	P2	S6	TP+	P6							
A6		RX1-		S5	TP-								
B6		TX1-		S3	RP-								
B5	TX1+	S2		RP+									
GND GROUP	GND	S1,S4,S7		GND									
		P13,P14,P15		+12V	1		+12V						
		P10,11,12		GND	2		GND						
F				P7,P8,P9	+5V	4	+5V						
				P4,P5,P6	GND	3	GND						
	A8	RX2+	P3	S6	TP+	P7							
	A9	RX2-		S5	TP-								
	B9	TX2-		S3	RP-								
B8	TX2+	S2		RP+									
GND GROUP	GND	S1,S4,S7		GND									
		P13,P14,P15		+12V	1		+12V						
		P10,11,12		GND	2		GND						
D				P7,P8,P9	+5V	4	+5V						
				P4,P5,P6	GND	3	GND						
	A11	RX3+	P4	S6	TP+	P8							
	A12	RX3-		S5	TP-								
	B12	TX3-		S3	RP-								
B11	TX3+	S2		RP+									
GND GROUP	GND	S1,S4,S7		GND									
		P13,P14,P15		+12V	1		+12V						
		P10,11,12		GND	2		GND						
C				P7,P8,P9	+5V	4	+5V						
				P4,P5,P6	GND	3	GND						
	GND GROUP: A1,A4,A7,A10,A13 B1,B4,B7,B10,B13												
A	DataStorageCables.com			DESC.	Mini SAS 4x TO 4*SAS drive cable rec. with power cable ass'y							A	
				P/N	C5629-1M				CUSTOMER P/N				
				APPROVED	CHECKED	DESIGNED	TOLERANCE	SCALE	1 = 1	UNIT	mm		
						SHIH		DATE	02/05/09	DWG NO:	DWG/RC/3018		
1		2		3		4		5		6			