



DataStorageCables.com	DESC.	4X FEMALE TO MiniSAS 4i PLUG CABLE ASSEMBLY	APPROVED	CHECKED	DESIGNED	TOLERANCE	SCALE	1 = 1	UNIT	mm	
	P/N	I5236-1M	CUSTOMER P/N	I5236-1M				DATE	10/31/07	DWG NO:	DWG\RC\2597

1	2		3		4	5	6	
REV.	REMARK		DATE	SIGN.				
WIRING DIAGRAM								
SAS4X FEMALE				MiniSAS4i PLUG				
REC.	PIN	SIGNAL	PLUG	PIN	SIGNAL			
P1	S1	RX0+	P2	A2	RX0+			
	S2	RX0-		A3	RX0-			
	S15	TX0-		B3	TX0-			
	S16	TX0+		B2	TX0+			
	S3	RX1+		A5	RX1+			
	S4	RX1-		A6	RX1-			
	S13	TX1-		B6	TX1-			
	S14	TX1+		B5	TX1+			
	S5	RX2+		A13	RX2+			
	S6	RX2-		A14	RX2-			
	S11	TX2-		B14	TX2-			
	S12	TX2+		B13	TX2+			
	S7	RX3+		A16	RX3+			
	S8	RX3-		A17	RX3-			
	S9	TX3-		B17	TX3-			
	S10	TX3+		B16	TX3+			
	GND GROUP			GND GROUP				
G1-G9,CONNECTOR SHELL			A1,A4,A7,A12,A15,A18 B1,B4,B7,B12,B15,B18					
DESC. 4X FEMALE TO MiniSAS 4i PLUG CABLE ASSEMBLY								
DataStorageCables.com				P/N I5236-1M		CUSTOMER P/N I5236-1M		
				APPROVED	CHECKED	DESIGNED SHIU	TOLERANCE	SCALE 1 = 1
				DATE 10/31/07	DWG NO: DWG\RC\2597			