

# NIGHTFALL SOUTH BEACH BLACKOUT



## TECHNICAL PROPERTIES

Composition	100% PES
Weight	390 g/m <sup>2</sup> ± 5%   11.5 oz/yd <sup>2</sup> ± 5%
Thickness	0.50 mm ± 5%   0.020 in ± 5%
Roll Width	2.5 m   98 in
Coating	Acrylic Foam Blackout Coating
UV Blockage	100%
Light Fastness	Class 4-5 (AATCC 16-2003)

\*Performance evaluations conducted by independent laboratories.

## CARE & MAINTENANCE



1. Vacuum clean for regular maintenance.
2. Do not use soap solution nor a damp cloth.
3. Do not wash.
4. Do not wring dry.
5. Do not bleach.
6. Do not dry clean nor use steam cleaning.

## MANUFACTURING



Use Only on  
Roll Direction



Ultrasonic Cut  
NOT Required

## INTERNATIONAL CERTIFICATIONS



The **Vertilux Collection** has all of the most important certificates in the industry. However, different certificates apply for different fabrics in our collection. Please ask our Customer Service Department about the certificates available for specific fabric patterns.

## APPLICATIONS



Roller  
Shades



Sliding  
Panels



Indoor Use  
Only



vertilux.com

**IMPORTANT:** The values and recommendations in this card are not contractual and can not be used as claim for order cancellations or returns. This technical data may vary at any time without previous notice. Color samples may not necessarily be an exact match of the material to be used to produce your order. Returns will not be accepted due to minor variations of color or texture.

© 2021, Vertilux, Ltd. All Rights Reserved. 6<sup>th</sup> Edition.