

DRAPES COLLECTION

NIGHTTIME

BLACKOUT



TECHNICAL PROPERTIES*

Composition	100% PES with Acrylic Coating
Weight	260 g/m ² ± 5% 7.66 oz/yd ² ± 5%
Roll Width	2.8 m ± 5% 110.2 in ± 5%
Fabric Construction	Coated
Fabric Coloring	Unbleached Non-colored
Yarn Type	100% Continuous Filaments Non-textured
Weave Type	Plain
Coating	Emulsion Acrylic
UV Blockage	100%
Light Fastness	ISO 105-B02 4 Xenotest Grade
Flame Retardant**	-

*Performance evaluations conducted by independent laboratories.

**Flame Retardant fabric available upon request. Minimum order quantity applies.

CARE & MAINTENANCE



1. Wash with cold water and a mild detergent solution.
2. Do not wring dry.
3. Do not tumble dry.
4. Do not bleach.
5. Do not dry clean nor use steam cleaning.
6. Iron at low temperature (230°F/110°C or below, fabric side only).

MANUFACTURING



Can be
Railroaded



Regular & Heat Cut
can be applied

INTERNATIONAL CERTIFICATIONS



The **Vertilux Collection** has all of the most important certificates in the industry. However, different certificates apply for different fabrics in our collection. Please ask our Customer Service Department about the certificates available for specific fabric patterns.

APPLICATIONS



Drapery



Indoor Use
Only



IMPORTANT: The values and recommendations in this card are not contractual and can not be used as claim for order cancellations or returns. This technical data may vary at any time without previous notice. Color samples may not necessarily be an exact match of the material to be used to produce your order. Returns will not be accepted due to minor variations of color or texture.

vertilux.com

© 2022. Vertilux, Ltd. All Rights Reserved. 1st Edition.