

ROLLUX COLLECTION SINGULAR BLACKOUT 3000 FR



TECHNICAL PROPERTIES

Composition	100% PES
Weight	350 g/m ² ± 5% 10.32 oz/yd ² ± 5%
Thickness	0.46 mm ± 5% 0.018 in ± 5%
Roll Width	3.0 m 118 in
Roll Length	30 m 33 yd
Light Fastness (Grey Scale Level)	6 Xenotest Grade
Flame Retardant*	NFPA 701

*Performance evaluations conducted by independent laboratories.

CARE & MAINTENANCE



1. Vacuum clean for regular maintenance.
2. Do not use soap solution nor a damp cloth.
3. Do not wash.
4. Do not wring dry.
5. Do not bleach.
6. Do not dry clean nor use steam cleaning.

MANUFACTURING



Use Only on Roll Direction Ultrasonic Cut NOT Required

INTERNATIONAL CERTIFICATIONS



The **Vertilux Collection** has all of the most important certificates in the industry. However, different certificates apply for different fabrics in our collection. Please ask our Customer Service Department about the certificates available for specific fabric patterns.

IMPORTANT: The values and recommendations in this card are not contractual and can not be used as claim for order cancellations or returns. This technical data may vary at any time without previous notice. Color samples may not necessarily be an exact match of the material to be used to produce your order. Returns will not be accepted due to minor variations of color or texture.

APPLICATIONS



Roller Shades Sliding Panels Indoor Use Only

Date: _____

App By: _____

Item Number: _____

Item Name: _____

Color Name & Number: _____

Supplier Name: _____

Supplier Item Name & Number: _____



vertilux.com