

DIAMANTE BLACKOUT



TECHNICAL PROPERTIES

Composition	100% PES Emulsion Acrylic Coating
Weight	320 g/m ² ± 10% 9.43 oz/yd ² ± 10%
Thickness	0.30 mm (± 3%) 0.011 in (± 3%)
Roll Width	2.0 m, 2.5 m, 3.0 m 78.74 in, 98 in, 118 in
Roll Length	40 m 44 yd
Light Fastness	3-4 Grade

*Performance evaluations conducted by independent laboratories.

CARE & MAINTENANCE



1. Vacuum clean for regular maintenance.
2. Do not wash.
3. Do not wring dry.
4. Do not bleach.
5. Do not dry clean nor use steam cleaning.

MANUFACTURING



Can be
Railroaded



Ultrasonic Cut
NOT Required

INTERNATIONAL CERTIFICATIONS



The **Vertilux Collection** has all of the most important certificates in the industry. However, different certificates apply for different fabrics in our collection. Please ask our Customer Service Department about the certificates available for specific fabric patterns.

APPLICATIONS



Roller
Shades



Indoor Use
Only

IMPORTANT: The values and recommendations in this card are not contractual and can not be used as claim for order cancellations or returns. This technical data may vary at any time without previous notice. Color samples may not necessarily be an exact match of the material to be used to produce your order. Returns will not be accepted due to minor variations of color or texture.



vertilux.com

© 2024, Vertilux, Ltd. All Rights Reserved. 1st Edition.