

SUNLUX PLUS



TECHNICAL PROPERTIES

Composition	-	100% Acrylic Masacril® Solution Dyed
Weight	-	290-310 ± 5% g/m ² 8.55-9.14 ± 5% oz/yd ²
Roll Width	-	1.20 m 47 in
Roll Length	-	50 m 54.68 yd
Light Fastness	-	7-8 Grade
Water Repellency	UNE EN 20811	360 mm
Finish	-	Sunlux® Protection

*Performance evaluations conducted by independent laboratories.

CARE & MAINTENANCE



1. Wipe gently with a wet sponge.
2. Vacuum clean for regular maintenance.
3. Hand wash with lukewarm water and a mild detergent solution.
4. Do not wring dry.
5. Do not bleach.
6. Do not dry clean nor use steam cleaning.
7. To protect the surface of the screen, please do not place any sharp items on the screen.
8. Wet cleaning, you may use water or gentle detergent cleaners (PH7-8.5). Please do not use acetone or polish that will damage the sunscreen.

INTERNATIONAL CERTIFICATIONS



The **Vertilux Collection** has all of the most important certificates in the industry. However, different certificates apply for different fabrics in our collection. Please ask our Customer Service Department about the certificates available for specific fabric patterns.

IMPORTANT: The values and recommendations in this card are not contractual and can not be used as claim for order cancellations or returns. This technical data may vary at any time without previous notice. Color samples may not necessarily be an exact match of the material to be used to produce your order. Returns will not be accepted due to minor variations of color or texture.

APPLICATIONS



Awnings



Canopies



Retractable Canopies



Pergolas



Umbrellas



Outdoor Upholstery



Indoor Upholstery



Marine Applications

MANUFACTURING



Can be Railroaded



Ultrasonic Cut NOT Required



vertilux.com

© 2025. Vertilux, Ltd. All Rights Reserved. 1st Edition.