

# DRAPES PRIMA COLLECTION

## IMPERIAL BLACKOUT



### TECHNICAL PROPERTIES\*

Composition	80% PES + 20% Foam Coated Emulsion Acrylic Coating
Weight	354g/m <sup>2</sup> ± 5%   10.44 oz/yd <sup>2</sup> ± 5%
Thickness	0.60 mm ± 2%   0.024 in ± 2%
Roll Width	2.8 m ± 5%   110.2 in ± 5%
Roll Length	32 m ± 5%   35 yd ± 5%
UV Blockage	100%
Light Fastness	Class 7-8
Flame Retardant**	-

\*Performance evaluations conducted by independent laboratories.

\*\*Flame Retardant fabric available upon request. Minimum order quantity applies.

### CARE & MAINTENANCE



1. Wash with cold water and a mild detergent solution.
2. Do not wring dry.
3. Do not tumble dry.
4. Do not bleach.
5. Do not dry clean nor use steam cleaning.
6. Iron at low temperature (230°F/110°C or below).

### MANUFACTURING



Use Only on  
Roll Direction



Regular & Heat Cut  
can be applied

### INTERNATIONAL CERTIFICATIONS



The **Vertilux Collection** has all of the most important certificates in the industry. However, different certificates apply for different fabrics in our collection. Please ask our Customer Service Department about the certificates available for specific fabric patterns.

### APPLICATIONS



Drapery



Indoor Use  
Only



vertilux.com

**IMPORTANT:** The values and recommendations in this card are not contractual and can not be used as claim for order cancellations or returns. This technical data may vary at any time without previous notice. Color samples may not necessarily be an exact match of the material to be used to produce your order. Returns will not be accepted due to minor variations of color or texture.

© 2024. Vertilux, Ltd. All Rights Reserved. 1<sup>st</sup> Edition.